



ConTEXT

commands

EN

ConTeXt

commands

en / english
March 12, 2010

`\about {1.} [2.]`

- 1 CONTENT
- 2 REFERENCE

`\adaptlayout [...,1...] [...,2.,...]`

- 1 NUMBER OPTIONAL
- 2 height = DIMENSION max
- lines = NUMBER

`\startalignment [...,*...] ... \stop`

- * inherits from `\setupalign`

`\appendix [...,1...] {2.}`

- 1 REFERENCE OPTIONAL
- 2 CONTENT

`\at {1.} {2.} [...3.]`

- 1 CONTENT
- 2 CONTENT
- 3 REFERENCE

`\atpage [...]`

- * REFERENCE

`\startbackground {*.} ... \stop`

- * CONTENT

`\blackrule [...,*.,...]`

- * inherits from `\setupblackrules`

`\blackrules [...,*.,...]`

- * inherits from `\setupblackrules`

`\blank [...,*...]`

- * small medium big nowhite back white disable force reset line halfline FORMULA fixed flexible none always outer joinedup

`\bookmark [1.] {2.}`

- 1 IDENTIFIER OPTIONAL
- 2 CONTENT

`\startbuffer [...] ... \stop`

- * IDENTIFIER OPTIONAL

`\startbuffer [...] ... \stopbuffer`

- * IDENTIFIER OPTIONAL

`\but [...]`

- * REFERENCE

`\button [...,1.,...] {2.} [...3.,...]`

- 1 inherits from `\setupbuttons`
- 2 CONTENT
- 3 REFERENCE

`\bypassblocks [...,1...] [...2.,...]`

- 1 IDENTIFIER OPTIONAL
- 2 IDENTIFIER

`\Cap {...}`
* CONTENT

`\CAP {...}`
* CONTENT

`\cap {...}`
* CONTENT

`\Caps {... * ... }`
* WORD

`\chapter [...1;...] {...2}`
1 REFERENCE OPTIONAL
2 CONTENT

`\character {...}`
* CONTENT

`\Character {...}`
* CONTENT

`\characters {...}`
* CONTENT

`\Characters {...}`
* CONTENT

`\chem {...1} {...2} {...3}`
1 CONTENT
2 CONTENT
3 CONTENT

`\clip [...,1...,...] {...2}`
1 inherits from `\setupclipping`
2 CONTENT

`\clonefield [...1] [...2;...] [...3] [...4;...]`
1 IDENTIFIER
2 IDENTIFIER
3 IDENTIFIER
4 IDENTIFIER OPTIONAL

`\startcolor [...] ... \stop`
* IDENTIFIER

`\column`

`\startcolumns [...,*...,...] ... \stop`
* inherits from `\setupcolumns`

`\startcombination [...] ... \stop`
* N*M

`\startcomment [...1] [...,2...,...] ... \stop`
1 IDENTIFIER OPTIONAL OPTIONAL
2 inherits from `\setupcomment`

```
\comparecolorgroup [...]  
* IDENTIFIER
```

```
\comparepalet [...]  
* IDENTIFIER
```

```
\completecombinedlist [..] [...,2,...]  
1 IDENTIFIER OPTIONAL  
2 inherits from \setupcombinedlist
```

```
\completelistoffloats
```

```
\completelistofsorts
```

```
\completelistofsynonyms
```

```
\completeregister [...,*,...]  
* inherits from \setupregister OPTIONAL
```

```
\startcomponent ... \stop  
* FILE NAME
```

```
\convertnumber {..} {..}  
1 CONTENT  
2 CONTENT
```

```
\copyfield [..] [...,2,...]  
1 IDENTIFIER  
2 IDENTIFIER
```

```
\correctwhitespace {...}  
* CONTENT
```

```
\coupledocument [..] [..] [..]  
1 IDENTIFIER  
2 file  
3 IDENTIFIER
```

```
\coupleregister [..] {..}  
1 TEXT OPTIONAL  
2 INDEX
```

```
\couplemarking [..] [..]  
1 IDENTIFIER  
2 IDENTIFIER
```

```
\couplepage [...,1,...] [...,2,...]  
1 IDENTIFIER  
2 option = doublesided  
before = COMMAND  
after = COMMAND
```

```
\couplepaper [...]  
* IDENTIFIER
```

```
\coupleregister [...]  
* IDENTIFIER
```

`\crlf`

`\currentdate [...*...]`
* inherits from \date

`\currentheadnumber`

`\date [...1...2...]`
1 d = NUMBER^{OPTIONAL}
m = NUMBER
y = NUMBER
2 day month year weekday d m y w dd mm yy space -- day+ d+ dd+ referral TEXT

`\decouplemarking [...]`
* IDENTIFIER

`\define [1] \2 {3}`
1 NUMBER ^{OPTIONAL}
2 CSNAME
3 CONTENT

`\defineblank [1] [2]`
1 IDENTIFIER
2 inherits from \setupblank

`\defineblock [...]`
* IDENTIFIER

`\definebodyfont [...1...2] [3] [...3...]`
1 5pt ... 12pt small big ^{OPTIONAL}
2 rm ss tt hw cg mm
3 tf = FILE
bf = FILE
sl = FILE
it = FILE
bs = FILE
bi = FILE
sc = FILE
mr = FILE
ex = FILE
mi = FILE
sy = FILE
ma = FILE
mb = FILE
mc = FILE
md = FILE

`\definebodyfont [1] [2] [3]`
1 IDENTIFIER
2 inherits from \setupbodyfont
3 inherits from \setupbodyfont

```

\definebodyfontenvironment [1.] [2.] [3.,.,.]
1 IDENTIFIER                OPTIONAL      OPTIONAL
2 5pt ... 12pt default
3 text      = DIMENSION
  script    = DIMENSION
  scriptscript = DIMENSION
  x         = DIMENSION
  xx        = DIMENSION
  a         = DIMENSION
  b         = DIMENSION
  c         = DIMENSION
  d         = DIMENSION
  small    = DIMENSION
  big      = DIMENSION
  interlinespace = DIMENSION
  em       = normal bold slanted boldslanted type cap small... COMMAND

```

```

\definebodyfont [1.] [2.] [3.]
1 inherits from \setupbodyfont
2 inherits from \setupbodyfont
3 IDENTIFIER

```

```

\definebuffer [*.]
* IDENTIFIER

```

```

\definecolor [1.] [2.,.,.]
1 IDENTIFIER
2 r = TEXT
  g = TEXT
  b = TEXT
  c = TEXT
  m = TEXT
  y = TEXT
  k = TEXT
  s = TEXT
  h = TEXT
  t = TEXT
  a = TEXT
  p = TEXT
  e = TEXT

```

```

\definecolorgroup [1.] [2.] [x:y:z=,.]
1 IDENTIFIER                OPTIONAL
2 rgb cmyk gray s
3 TRIPLET

```

```

\definecombinedlist [1.] [2.,.,.] [3.,.,.]
1 IDENTIFIER                OPTIONAL
2 LIST
3 inherits from \setupcombinedlist

```

```

\defineconversion [1.] [2.]
1 IDENTIFIER
2 COMMAND TEXT

```

```

\definedescription [1.] [2.,.,.]
1 IDENTIFIER                OPTIONAL
2 inherits from \setupdescriptions

```

```

\definedfont [*.]
* inherits from \definefont

```

```

\defineenumeration [1.,.,.] [2.] [3.,.,.]
1 IDENTIFIER                OPTIONAL      OPTIONAL
2 IDENTIFIER
3 inherits from \setupenumerations

```

```
\definefield [1.] [2.] [3.] [...4,...] [5.]
1 IDENTIFIER OPTIONAL
2 text line push check radio combo choice popup
3 IDENTIFIER
4 IDENTIFIER
5 IDENTIFIER
```

```
\definefieldstack [1.] [...2,...] [...3,...]
1 IDENTIFIER
2 IDENTIFIER
3 inherits from \setupfields
```

```
\definefiguresymbol [1.] [2.] [...3,...]
1 IDENTIFIER OPTIONAL
2 TEXT
3 inherits from \setupexternalfigures
```

```
\definefloat [1.] [2.]
1 SINGULAR NAME
2 PLURAL NAME
```

```
\definefont [1.] [2.] [3.]
1 IDENTIFIER OPTIONAL
2 FILE
3 TEXT
```

```
\definefontfeature [1.] [2.] [3.]
1 TEXT OPTIONAL
2 IDENTIFIER
3 compose = no yes
mode = node base
tlig = no yes
trep = no yes
script = IDENTIFIER
language = IDENTIFIER
..tag.. = no yes
```

```
\definefonthandling [1.] [2.] [3.]
1 IDENTIFIER
2 IDENTIFIER
3 type = hanging hz spacing tag
right = NUMBER
left = NUMBER
factor = NUMBER
min = NUMBER
max = NUMBER
step = NUMBER
```

```
\definefontsynonym [1.] [2.] [3.]
1 TEXT OPTIONAL
2 IDENTIFIER
3 encoding = IDENTIFIER
features = IDENTIFIER
handling = IDENTIFIER
mapping = IDENTIFIER
```

```
\defineframed [1.] [...2,...]
1 IDENTIFIER OPTIONAL
2 inherits from \setupframedtexts
```

```
\defineframedtext [1.] [...2,...]
1 IDENTIFIER OPTIONAL
2 inherits from \setupframedtexts
```

```
\definehead [1.] [2.]
1 IDENTIFIER
2 SECTION
```

`\defineindenting [..] [..,2,..]`

1 IDENTIFIER
2 inherits from \setupindentations

`\defineinteractionmenu [...;...] [..,2,..]`

1 left right top bottom IDENTIFIER OPTIONAL
2 inherits from \setupinteractionmenu

`\defineinteractionmenu [..] [..] [..,3,..]`

1 left right top bottom IDENTIFIER OPTIONAL OPTIONAL
2 left right top bottom IDENTIFIER
3 inherits from \setupinteractionmenu

`\definelabel [..] [..,2,..]`

1 IDENTIFIER
2 text = TEXT
location = inmargin intext
way = bytext bycd:section
blockway = yes no
headstyle = normal bold slanted boldslanted type cap small... COMMAND
headcolor = IDENTIFIER
before = COMMAND
after = COMMAND

`\definelist [..] [..] [..,3,..]`

1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 inherits from \setuplist

`\definelogo [..] [..] [..] [..,4,..]`

1 IDENTIFIER
2 top header footer bottom
3 none page leftedge leftmargin left middle right rightmargin rightedge
4 command = COMMAND TEXT
state = start stop

`\definemakeup [..] [..,2,..]`

1 IDENTIFIER
2 inherits from \setupmakeup

`\definemarking [..] [..]`

1 IDENTIFIER OPTIONAL
2 IDENTIFIER

`\defineoutput [..] [..,2,..]`

1 IDENTIFIER
2 IDENTIFIER

`\defineoverlay [...;...] [..]`

1 IDENTIFIER
2 COMMAND

`\definepalet [..] [..,2,..]`

1 IDENTIFIER
2 IDENTIFIER = IDENTIFIER

`\definepapersize [..] [..,2,..]`

1 IDENTIFIER
2 width = DIMENSION
height = DIMENSION
offset = DIMENSION
scale = NUMBER

`\defineparagraphs [..1.] [..,2,...]`

1 IDENTIFIER
2 n = NUMBER
rule = on off
height = fit DIMENSION
before = COMMAND
after = COMMAND
inner = COMMAND
distance = DIMENSION
tolerance = verystRICT strict tolerant verytolerant stretch
align = inner outer left right flushleft flushright middle center normal no yes

`\defineprofile [..1;...] [..,2,...]`

1 IDENTIFIER
2 IDENTIFIER

`\defineprogram [..1.] [..2.] [..3.]`

1 IDENTIFIER
2 TEXT
3 TEXT

`\definereference [..1.] [..,2,...]`

1 IDENTIFIER
2 REFERENCE

`\definereferenceformat [..1.] [..,2,...]`

1 IDENTIFIER
2 left = TEXT
right = TEXT
text = TEXT
label = IDENTIFIER

`\definereferencelist [..1.] [..,2,...]`

1 IDENTIFIER OPTIONAL
2 *inherits from* \setupreferencelist

`\defineregister [..1.] [..2.]`

1 SINGULAR NAME
2 PLURAL NAME

`\definesection [..*.]`

* IDENTIFIER

`\definesectionblock [..1.] [..,2,...]`

1 *inherits from* \setupsectionblock OPTIONAL
2 *inherits from* \setupsectionblock

`\definesorting [..1.] [..2.] [..3.]`

1 SINGULAR NAME OPTIONAL
2 PLURAL NAME
3 COMMAND

`\definestartstop [..1.] [..,2,...]`

1 IDENTIFIER
2 before = COMMAND
after = COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
commands = COMMAND

`\definesubfield [..1.] [..2.] [..,3,...]`

1 IDENTIFIER
2 IDENTIFIER
3 IDENTIFIER

`\definesymbol [1.] [2.]`

- 1 IDENTIFIER
- 2 TEXT

`\definesynonyms [1.] [2.] [3.] [4.]`

- 1 SINGULAR NAME OPTIONAL
- 2 PLURAL NAME
- 3 COMMAND
- 4 COMMAND

`\definetabletemplate [1.] [2.] [3.] [4.]`

- 1 IDENTIFIER OPTIONAL OPTIONAL
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\definetabulate [1.] [2.] [3.]`

- 1 IDENTIFIER OPTIONAL
- 2 IDENTIFIER
- 3 TEXT

`\definetext [1.] [2.] [3.] [4.] [5.]`

- 1 IDENTIFIER OPTIONAL OPTIONAL
- 2 header footer
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\definetype [1.] [...2...]`

- 1 IDENTIFIER
- 2 *inherits from* \setuptype

`\definetypface [1.] [2.] [3.] [4.] [5.] [6.]`

- 1 TEXT OPTIONAL OPTIONAL
- 2 rm ss tt mm hw cg
- 3 IDENTIFIER
- 4 IDENTIFIER
- 5 IDENTIFIER
- 6 features = IDENTIFIER
rscale = NUMBER
encoding = IDENTIFIER
text = IDENTIFIER

`\definetyping [1.] [...2...]`

- 1 *inherits from* \setuptyping
- 2 *inherits from* \setuptyping

`\defineversion [1.] [...2...]`

- 1 IDENTIFIER
- 2 NUMBER

`\description {1.} 2.`

- 1 CONTENT
- 2 NOTHING

`\determineheadnumber [*.]`

- * SECTION

`\determinelistcharacteristics [...1...] [...2...]`

- 1 IDENTIFIER OPTIONAL
- 2 *inherits from* \setuplist

```
\disableinteractionmenu [1.] [2...;...]
1 left right top bottom IDENTIFIER
2 REFERENCE
```

```
\startdocument [...]. ... \stop
* IDENTIFIER
```

```
\emptylines [...].
* NUMBER
```

```
\enumeration ...
* NOTHING
```

```
\startenvironment ... .. \stop
* FILE NAME
```

```
\externalfigure [1.] [2...;...]
1 FILE OPTIONAL
2 inherits from \setupexternalfigures
```

```
\startfact 1. 2. 3. ... \stop
1 NOTHING
2 NOTHING
3 NOTHING
```

```
\field [...].
* IDENTIFIER
```

```
\fieldstack [1.] [2...;...] [3...;...]
1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 inherits from \setupfields
```

```
\startfigure [1.] [2.] [3...;...] ... \stop
1 IDENTIFIER
2 FILE
3 factor = NUMBER
frame = on off
```

```
\fillinfield [1.] {2.}
1 TEXT OPTIONAL
2 CONTENT
```

```
\fillinline [1...;...] 2.
1 inherits from \setupfillinlines
2 NOTHING
```

```
\fillinrules [1...;...] {2.} {3.}
1 inherits from \setupfillinrules OPTIONAL
2 CONTENT
3 CONTENT
```

```
\fillintext [1...;...] {2.} {3.}
1 inherits from \setupfillinrules OPTIONAL
2 CONTENT
3 CONTENT
```

```
\fitfield [...].
* IDENTIFIER
```

`\fixedspaces`

`\startfloat text [.1.] [.2.] {.3.} {.4.} ... \stopfloat`
1 left right high middle low offset tall
2 REFERENCE
3 CONTENT
4 CONTENT

`\followprofile {.1.} [.2.]`
1 CONTENT
2 TEXT

`\followprofileversion {.1.} [.2.] [.3.]`
1 CONTENT
2 TEXT
3 IDENTIFIER

`\followversion {.1.} [.2.]`
1 CONTENT
2 TEXT

`\footnote [.1.] {.2.}`
1 REFERENCE OPTIONAL
2 CONTENT

`\footnotetext [.1.] {.2.}`
1 REFERENCE OPTIONAL
2 CONTENT

`\forceblocks [...1;...] [...2;...]`
1 IDENTIFIER OPTIONAL
2 IDENTIFIER

`\startformula ... \stopformula`

`\fraction {.1.} {.2.}`
1 CONTENT
2 CONTENT

`\framed [...1;...] {.2.}`
1 inherits from `\setupframed`
2 CONTENT

`\startframedtext [.1.] [...2;...] ... \stopframedtext`
1 left right middle none OPTIONAL OPTIONAL
2 inherits from `\setupframedtexts`

`\from [...]`
* REFERENCE

`\getbuffer [...]`
* IDENTIFIER OPTIONAL

`\getmarking [.1.] [.2.]`
1 IDENTIFIER
2 first last previous both all current

`\godown [...]`
* DIMENSION

`\goto {..} {..} [...3,...]`

1 CONTENT
2 CONTENT
3 REFERENCE

`\gotobox {..} [...2,...]`

1 CONTENT
2 REFERENCE

`\graycolor [...]`

* TEXT

`\grid [...,*...]`

* x = NUMBER
y = NUMBER
nx = NUMBER
ny = NUMBER
dx = NUMBER
dy = NUMBER
xstep = NUMBER
ystep = NUMBER
offset = yes no
factor = NUMBER
scale = NUMBER
unit = cm pt em mm ex es in
location = left middle

`\hairline`

`\head [...,*...]`

* REFERENCE OPTIONAL

`\headnumber [...]`

* SECTION OPTIONAL

`\headtext {...}`

* CONTENT

`\hideblocks [...1,...] [...2,...]`

1 IDENTIFIER OPTIONAL
2 IDENTIFIER

`\starthiding ... \stop`

`\high {...}`

* CONTENT

`\h1 [...]`

* NUMBER

`\in {..} {..} [...3]`

1 CONTENT
2 CONTENT
3 REFERENCE

`\indentation ...`

* NOTHING

`\indenting [...,*...]`

* never none not no yes always first next small medium big normal odd even DIMENSION

```
\inframed [...,1,...] {...}
1 inherits from \setupinframed
2 CONTENT
```

```
\ininner [...1] [...2] {...3}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inleft [...1] [...2] {...3}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inline [...*]
* REFERENCE
```

```
\inmargin [...1] [...2] {...3}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inothmargin [...1] [...2] {...3}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inouter [...1] [...2] {...3}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\inright [...1] [...2] {...3}
1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT
```

```
\installlanguage [...1] [...,2,...]
1 IDENTIFIER
2 spacing = packed broad
leftthyphenmin = NUMBER
rightthyphenmin = NUMBER
state = start stop
leftsentence = COMMAND
rightsentence = COMMAND
leftsubsentence = COMMAND
rightsubsentence = COMMAND
leftquote = COMMAND
rightquote = COMMAND
leftquotation = COMMAND
rightquotation = COMMAND
leftspeech = COMMAND
middlespeech = COMMAND
rightspeech = COMMAND
limittext = TEXT
date = TEXT
compoundhyphen = COMMAND
leftcompoundhyphen = COMMAND
rightcompoundhyphen = COMMAND
default = IDENTIFIER
```

```
\interactionbar [...,*,...]
* inherits from \setupinteractionbar
```

```
\interactionbuttons [...,1,...] [...2,...]
1 inherits from \setupinteractionbar
2 IDENTIFIER
```

```
\startinteractionmenu [...] ... \stop
* IDENTIFIER
```

```
\item [...,*...]
* REFERENCE OPTIONAL
```

```
\startitemgroup [.1.] [...,2...] [...,3...,...] ... \stopitemgroup
1 IDENTIFIER OPTIONAL OPTIONAL
2 a A KA n N m r R KR NUMBER continue standard broad serried packed stopper joinedup atmargin inmargin intro columns
text paragraph repeat
3 inherits from \setupitemgroup
```

```
\items [...,1...,...] {...2. ...}
1 inherits from \setupitems
2 CONTENT
```

```
\its [...,*...]
* REFERENCE OPTIONAL
```

```
\keepblocks [...,1...] [...,2...]
1 IDENTIFIER OPTIONAL
2 all IDENTIFIER
```

```
\labeling [...]
* REFERENCE OPTIONAL
```

```
\labels [...]
* IDENTIFIER
```

```
\labeltext {...}
* CONTENT
```

```
\language [...]
* nl fr en uk de es cz ..
```

```
\leftaligned {...}
* CONTENT
```

```
\startlegend [.1.] .2. .3. .4. ... \stop
1 two OPTIONAL
2 NOTHING
3 NOTHING
4 NOTHING
```

```
\startline [...] ... \stop
* REFERENCE
```

```
\startlinecorrection ... \stop
```

```
\startlinenumbering [...] ... \stop
* continue
```

```
\startlines ... \stop
```

```
\listsymbol [.1.] {...2.}
1 IDENTIFIER
2 CONTENT
```

`\loadsorts`

`\loadsynonyms`

`\startlocal ... \stop`

`\startlocalenvironment ... \stop`

`\startlocalfootnotes ... \stop`

`\logfields`

`\lohi [1.] {2.} {3.}`

1 low OPTIONAL
2 CONTENT
3 CONTENT

`\low {...}`

* CONTENT

`\mainlanguage [...]`

* nl fr en uk de es cz ..

`\startmakeup [1.] [...,2,...] ... \stop`

1 IDENTIFIER OPTIONAL
2 inherits from \setupmakeup

`\mapfontsize [1.] [2.]`

1 DIMENSION
2 DIMENSION

`\mar [...,1,...] {2.}`

1 REFERENCE OPTIONAL
2 CONTENT

`\startmarginblock ... \stop`

`\startmarginrule [...] ... \stop`

* NUMBER

`\margintext [1.] [2.] {3.}`

1 + - low OPTIONAL OPTIONAL
2 REFERENCE
3 CONTENT

`\marking [1.] {2.}`

1 IDENTIFIER
2 CONTENT

`\markversion`

`\mathematics {...}`

* CONTENT

`\mediaeval {...}`

* CONTENT

`\midaligned {...}`
* CONTENT

`\mirror {...}`
* CONTENT

`\MONTH {...}`
* CONTENT

`\month {...}`
* CONTENT

`\moveongrid [...*,...]`
* standard top bottom -top -both -bottom TEXT high middle low page broad fit depth line reset none DIMENSION

`\name {...}`
* CONTENT

`\startname makeup ... \stopname`

`\startnarrower [...*,...]` ... `\stop`
* left middle right ~~left~~ ~~right~~ ~~middle~~ -right -none

`\nextsection`

`\nocap {...}`
* CONTENT

`\noheaderandfooterlines`

`\noindenting`

`\nolist {...}`
* CONTENT

`\nomarking {...}`
* CONTENT

`\nomoreblocks`

`\nomorefiles`

`\nop`

`\nospace`

`\note [...]`
* REFERENCE

`\notopandbottomlines`

`\nowhitespace`

`\numbers {...}`
* CONTENT

`\startopposite ... \stop`

`\overbar {...}`
* CONTENT

`\overbars {...}`
* WORD

`\startoverlay {...} {...} ... \stop`
1 CONTENT
2 CONTENT

`\overstrike {...}`
* CONTENT

`\overstrikes {...}`
* WORD

`\startoverview [...;...] ... \stop`
* IDENTIFIER

`\packed`

`\page [...;...]`
* `yes` `makeup` `no` `preference` `bigpreference` `left` `right` `disable` `last` `quadruple` `even` `odd` `blank` `empty` `reset` `start` `stop`

`\pagereference [...]`
* REFERENCE

`\pagetype [...]`
* IDENTIFIER

`\paragraph`

`\part [...1;...] {...2}`
1 REFERENCE OPTIONAL
2 CONTENT

`\periods [...]`
* NUMBER

`\placebookmarks [...1;...] [...2;...]`
1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER `all`

`\placecombinedlist [...1] [...2;...]`
1 IDENTIFIER OPTIONAL
2 `inherits from \setupcombinedlist`

`\placecombinedlist [...1] [...2;...]`
1 IDENTIFIER OPTIONAL
2 `inherits from \setupcombinedlist`

```
\placefloat [...1.] [...2;3...] {...4.} {...5.}
1 left right here top bottom left inright inmargin margin leftmargin rightmargin leftedge rightedge innermargin
  outermargin inneredge outeredge inner outer line high low fit page leftpage rightpage opposite always auto force
  tall reset line height depth split 90 180 270
2 REFERENCE
3 CONTENT
4 CONTENT
```

```
\placefootnotes [...*.;...]
* inherits from \setupfootnotes
```

```
\placeformula [...1.;...] {...2.} $$3...$$
1 REFERENCE          OPTIONAL  OPTIONAL
2 CONTENT
3 DISPLAY MATH
```

```
\placelegend {...1.} {...2.}
1 CONTENT
2 CONTENT
```

```
\placelist [...1.;...] [...2.;...]
1 IDENTIFIER          OPTIONAL
2 inherits from \setuplist
```

```
\placelistoffloats
```

```
\placelistofsorts
```

```
\placelistofsynonyms
```

```
\placelocalfootnotes [...*.;...]
* inherits from \setupfootnotes OPTIONAL
```

```
\placelogos [...*.;...]
* IDENTIFIER          OPTIONAL
```

```
\placeongrid [...1.] {...2.}
1 inherits from \setupongrid
2 CONTENT
```

```
\placeontopofeachother {...1.} {...2.}
1 CONTENT
2 CONTENT
```

```
\placereferencelist [...*.;...]
* IDENTIFIER
```

```
\placeregister [...1.] [...2.;...]
1 IDENTIFIER          OPTIONAL
2 inherits from \setupregister
```

```
\placeregister [...*.;...]
* inherits from \setupregister
```

```
\placesidebyside {...1.} {...2.}
1 CONTENT
2 CONTENT
```


`\referral [..,*.,...]`

* bet = TEXT
ken = TEXT
dat = TEXT
van = TEXT
aan = TEXT
ref = TEXT

`\referraldate`

`\register [.1.] {..+.2.+..}`

1 TEXT OPTIONAL
2 INDEX

`\reservefloat [..,1.,...] [.2.] [...,3...] {.4.}`

1 height = DIMENSION OPTIONAL OPTIONAL OPTIONAL
width = DIMENSION
frame = on off
2 TEXT
3 REFERENCE
4 CONTENT

`\reset [...,*.,...]`

* IDENTIFIER

`\resetmarking [.*.]`

* IDENTIFIER

`\resettextrcontent [.1.] [.2.] [.3.]`

1 top header text footer bottom OPTIONAL
2 text margin edge
3 lefttext middletext righttext

`\rightaligned {.*.}`

* CONTENT

`\Romannumerals {.*.}`

* CONTENT

`\romannumerals {.*.}`

* CONTENT

`\rotate [..,1.,...] {.2.}`

1 inherits from ~~from~~ `\setuprotate`
2 CONTENT

`\scale [..,1.,...] {.2.}`

1 sx = NUMBER OPTIONAL
sy = NUMBER
2 CONTENT

`\screen`

`\section [...,1...] {.2.}`

1 REFERENCE OPTIONAL
2 CONTENT

`\seeregister [.1.] {.2.} {..+.3.+..}`

1 TEXT OPTIONAL
2 CONTENT
3 INDEX

```
\selectblocks [...1;...] [...2;...] [...3.]
1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 criterium = all SECTION
```

```
\selectpaper [...,*,...]
* family = 1 2
```

```
\selectversion
```

```
\settextcontent [...1.] [...2.] [...3.] [...4.] [...5.]
1 top header text footer bottom OPTIONAL OPTIONAL OPTIONAL
2 text margin edge
3 TEXT SECTION date MARK pagenumber
4 TEXT SECTION date MARK pagenumber
5 TEXT SECTION date MARK pagenumber
```

```
\setupalign [...,*,...]
* width left right middle inner outer wide broad height bottom line reset hanging nohanging hyphenated
nothyphenated lessshyphenation morehyphenation new old normal yes no flushleft flushright flushouter flushinner
center hz nohz spacing nospacing tolerant verytolerant stretch lefttoright righttoleft
```

```
\setuparranging [...,*,...]
* disable 2*16 2*8 2*4 2*2 2**2 2*2*4 2*4*2 2UP 2DOWN 2SIDE 2TOP mirrored rotated doublesided negative background 90
180 270
```

```
\setupbackground [...,*,...]
* leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
before = COMMAND
after = COMMAND
state = start stop
inherits from \setupframed
```

```
\setupbackgrounds [...1.] [...2;...] [...3.,...]
1 top header TEXT footer bottom pagepaper leftpage rightpage
2 leftedge leftmargin TEXT rightmargin rightedge
3 state = start stop cd:repeat
inherits from \setupframed
```

```
\setupblackrules [...,*,...]
* width = DIMENSION max
height = DIMENSION max
depth = DIMENSION max
alternative = ab
distance = DIMENSION
n = NUMBER
color = IDENTIFIER
```

```
\setupblank [...*...]
* normal default standard line halfline DIMENSION big medium small fixed flexible global unknown
```

```
\setupblock [...1;...] [...2.,...]
1 IDENTIFIER
2 before = COMMAND
after = COMMAND
inner = COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
file = FILE
```

```
\setupbodyfont [...,*,...]
* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt ... 12pt
```

`\setupbodyfontenvironment` [¹.] [².] [³.,.,.]

1 inherits from `\definebodyfontenvironment` OPTIONAL
2 inherits from `\definebodyfontenvironment`
3 inherits from `\definebodyfontenvironment`

`\setupbottom` [¹.] [².,.,.]

1 inherits from `\setupheader`
2 inherits from `\setupheader`

`\setupbottomtexts` [¹.] [².] [³.]

1 `text margin edge` OPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber

`\setupbuffer` [¹.] [².,.,.]

1 IDENTIFIER OPTIONAL
2 paragraph = NUMBER
before = COMMAND
after = COMMAND

`\setupbuttons` [¹.,.,*.,.]

* state = start stop
inherits from `\setupframed`

`\setupcapitals` [¹.,.,*.,.]

* title = yes no
sc = yes no

`\setupcaption` [¹.] [².,.,.]

1 IDENTIFIER
2 inherits from `\setupcaptions`

`\setupcaptions` [¹.,.,*.,.]

* location = top bottom none high low middle left middle right lefthanging righthanging leftmargin rightmargin
innermargin outermargin
width = fit broad max DIMENSION
minwidth = fit DIMENSION
headstyle = normal bold slanted boldslanted type cap small... COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
number = yes no none
inbetween = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
conversion = numbers characters Characters romannumerals Romannumerals
way = bytext bycd:section
separator = TEXT
stopper = TEXT
command = COMMAND
distance = DIMENSION

`\setupclipping` [¹.,.,*.,.]

* state = start stop
n = NUMBER
nx = NUMBER
ny = NUMBER
x = NUMBER
y = NUMBER
sx = NUMBER
sy = NUMBER
width = DIMENSION
height = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
offset = DIMENSION
leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
mp = IDENTIFIER

`\setupcolor [..*]`

* IDENTIFIER

`\setupcolors [..,*.,..]`

* state = start stop global local
conversion = yes no always never
reduction = yes no
rgb = yes no
cmyk = yes no
mpcmyk = yes no
mpspot = yes no
factor = yes no
textcolor = IDENTIFIER
split = c m y k p s no IDENTIFIER
criterium = all none
intent = none overprint knockout

`\setupcolumns [..,*.,..]`

* n = NUMBER OPTIONAL
ntop = NUMBER
rule = on off
height = DIMENSION
tolerance = verystrict strict tolerant verytolerant stretch
distance = DIMENSION
balance = yes no
align = text inner outer left right flushleft flushright middle center normal no yes
blank = fixed halflines line flexible big medium small
option = background
direction = left right
inherits from \setupframed

`\setupcombinations [..,*.,..]`

* before = COMMAND
inbetween = COMMAND
after = COMMAND
distance = DIMENSION
height = DIMENSION fit
width = DIMENSION fit
location = top middle bottom left right
align = inner outer left right flushleft flushright middle center normal no yes
style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER

`\setupcombinedlist [..1.] [..,2.,..]`

1 IDENTIFIER
2 level = 1 2 3 4 SECTION current
inherits from \setuplist

`\setupcomment [..,*.,..]`

* state = start stop
width = DIMENSION
height = DIMENSION
color = IDENTIFIER
title = TEXT
space = yes no
symbol = normal New Balloon Addition Help Paragraph Key IDENTIFIER
option = max buffer
margin = DIMENSION
distance = DIMENSION

`\setupdescriptions [...1,...] [...2,...]`

```
1 IDENTIFIER OPTIONAL
2 style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
width = fit broad DIMENSION
distance = DIMENSION
sample = TEXT
text = TEXT
closesymbol = TEXT
closecommand = \...#1
closesymbol = TEXT
titleleft = TEXT
titleright = TEXT
titledistance = DIMENSION
titlestyle = normal bold slanted boldslanted type cap small... COMMAND
titlecolor = IDENTIFIER
align = inner outer left right flushleft flushright middle center normal no yes
margin = standard yes no DIMENSION
location = left right top serried inmargin inleft inright hanging
headstyle = normal bold slanted boldslanted type cap small... COMMAND
headcolor = IDENTIFIER
headcommand = COMMAND
hang = fit broad NUMBER
before = COMMAND
inbetween = COMMAND
after = COMMAND
indentnext = yes no
indenting = never none not no yes always first next small medium big normal odd even DIMENSION
command = COMMAND
```

`\setupenumerations [...1,...] [...2,...]`

```
1 IDENTIFIER OPTIONAL
2 inherits from \setupdescriptions
```

`\setupexternalfigures [.*.]`

```
* scale = NUMBER
yscale = NUMBER
yscale = NUMBER
factor = max fit broad
wfactor = NUMBER max broad fit
hfactor = NUMBER max broad fit
width = DIMENSION
height = DIMENSION
frame = on off
preset = yes no
display = FILE
preview = yes no
repeat = yes no
object = yes no
type = eps mps pdf tif png jpg mov cd:tex
method = eps mps pdf tif png jpg mov cd:tex
option = frame empty test
frames = on off
ymax = NUMBER
xmax = NUMBER
directory = TEXT
location = local global default none
maxwidth = DIMENSION
maxheight = DIMENSION
conversion = TEXT
prefix = TEXT
```

`\setupfield [.1.] [...2,...] [...3,...] [...4,...] [...5,...]`

```
1 IDENTIFIER
2 label horizontal vertical frame
3 inherits from \setupfields
4
5
```

```

\setupfields [...1...] [...2...] [...3...] [...4...]
1 reset label horizontal vertical frame
2 n = NUMBER
  distance = DIMENSION
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  color = IDENTIFIER
  style = normal bold slanted boldslanted type cap small... COMMAND
  align = inner outer left right flushleft flushright middle center normal no yes
  option = readonly required protected sorted unavailable hidden printable
  clickin = REFERENCE
  clickout = REFERENCE
  regionin = REFERENCE
  regionout = REFERENCE
  afterkey = REFERENCE
  format = REFERENCE
  validate = REFERENCE
  calculate = REFERENCE
  fieldoffset = DIMENSION
  fieldframecolor = IDENTIFIER
  fieldbackgroundcolor = IDENTIFIER
  inherits from \setupframed
3 inherits from \setupfields
4 inherits from \setupfields

```

```

\setupfillinlines [...*...]
* width = DIMENSION
  margin = DIMENSION
  distance = DIMENSION
  before = COMMAND
  after = COMMAND

```

```

\setupfillinrules [...*...]
* width = fit broad DIMENSION
  distance = DIMENSION
  before = COMMAND
  after = COMMAND
  style = normal bold slanted boldslanted type cap small... COMMAND
  n = NUMBER
  interlinespace = small medium big
  separator = TEXT

```

```

\setupfloat [...1...] [...2...]
1 IDENTIFIER
2 height = DIMENSION
  width = DIMENSION
  maxheight = DIMENSION
  maxwidth = DIMENSION
  minwidth = DIMENSION
  default = IDENTIFIER
  pageboundaries = LIST
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  location = left middle right
  inherits from \setupframed

```

```

\setupfloats [...,*... ]
* location = left right middle
width = fit DIMENSION
before = COMMAND
after = COMMAND
margin = DIMENSION
spacebefore = small medium big none
spaceafter = small medium big none
sidespacebefore = small medium big none
sidespaceafter = small medium big none
indentnext = yes no
ntop = NUMBER
nbottom = NUMBER
nlines = NUMBER
default = IDENTIFIER
tolerance = 0 1 2
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
sidealign = normal line
numbering = yes nocheck
inherits from \setupframed

```

```

\setupfloatsplitting [...,*... ]
* conversion = numbers characters Characters romannumerals Romannumerals
lines = NUMBER

```

```

\setupfonthandling [.1.] [.2.]
1 IDENTIFIER
2 inherits from \definefonthandling

```

```

\setupfontsynonym [.1.] [.2.]
1 IDENTIFIER
2 inherits from \definefontsynonym

```

```

\setupfooter [.1.] [...,*... ]
1 inherits from \setupheader
2 inherits from \setupheader

```

```

\setupfootertexts [.1.] [.2.] [.3.]
1 text margin edge OPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber

```

```

\setupfootnotedefinition [...,*... ]
* inherits from \setupdescriptions

```

```

\setupfootnotes [...,*... ]
* conversion = numbers characters Characters romannumerals Romannumerals
way = bytext bycd:section
location = page TEXT columns firstcolumn lastcolumn high none
rule = on off
before = COMMAND
after = COMMAND
width = DIMENSION
height = DIMENSION
bodyfont = 5pt ... 12pt small big
style = normal bold slanted boldslanted type cap small... COMMAND
distance = DIMENSION
columndistance = DIMENSION
margindistance = DIMENSION
n = NUMBER
numbercommand = \...#1
textcommand = \...#1
split = tolerant strict verystrict NUMBER
textstyle = normal bold slanted boldslanted type cap small... COMMAND
textcolor = IDENTIFIER
interaction = yes no
factor = NUMBER
inherits from \setupframed

```

```
\setupforms [.,.,*.,..]
* method = HTML FDF
```

```
\setupformulas [.,.,*.,..]
* location = left right
left = TEXT
right = TEXT
align = inner outer left right flushleft flushright middle center normal no yes
option = middle
strut = yes no
distance = DIMENSION
margin = DIMENSION standard yes no
align = flushleft flushright middle center
leftmargin = DIMENSION
rightmargin = DIMENSION
indentnext = yes no
alternative = IDENTIFIER
spacebefore = DIMENSION
after = DIMENSION
separator = TEXT
conversion = numbers characters Characters romannumerals Romannumerals TEXT
```

```
\setupframed [1.] [.,.,2.,..]
1 IDENTIFIER OPTIONAL
2 height = fit broad DIMENSION
width = fit broad fixed local DIMENSION
autowidth = yes no force
offset = none overlay default DIMENSION
location = depth hanging high lohi low top middle bottom keep
option = none empty
strut = yes no global local
align = inner outer left right flushleft flushright middle center normal no yes
bottom = COMMAND
top = COMMAND
frame = on off none overlay
topframe = on off
bottomframe = on off
leftframe = on off
rightframe = on off
frameoffset = DIMENSION
framedepth = DIMENSION
framecorner = round rectangular
frameradius = DIMENSION
framecolor = IDENTIFIER
background = screen color none foreground IDENTIFIER
backgroundscreen = NUMBER
backgroundcolor = IDENTIFIER
backgroundoffset = frame DIMENSION
backgrounddepth = DIMENSION
backgroundcorner = round rectangular
backgroundradius = DIMENSION
depth = DIMENSION
corner = round rectangular
radius = DIMENSION
empty = yes no
foregroundcolor = IDENTIFIER
foregroundstyle = normal bold slanted boldslanted type cap small... COMMAND
rulethickness = DIMENSION
```

```
\setupframedtexts [1.] [.,.,2.,..]
1 IDENTIFIER OPTIONAL
2 bodyfont = 5pt ... 12pt small big
style = normal bold slanted boldslanted type cap small... COMMAND
left = COMMAND
right = COMMAND
before = COMMAND
after = COMMAND
inner = COMMAND
linecorrection = on off
depthcorrection = on off
margin = standard yes no
location = left right middle none
indenting = never none not no yes always first next small medium big normal odd even DIMENSION
inherits from \setupframed
```

`\setuphead [...1,...] [...2,...]`

1 SECTION
2 style = normal bold slanted boldslanted type cap small... COMMAND
textstyle = normal bold slanted boldslanted type cap small... COMMAND
numberstyle = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
textcolor = IDENTIFIER
numbercolor = IDENTIFIER
number = yes no
ownnumber = yes no
page = left right yes
continue = yes no
header = none empty high nomarking
text = none empty high nomarking
footer = none empty high nomarking
before = COMMAND
inbetween = COMMAND
after = COMMAND
alternative = normal inmargin middle TEXT
hang = none broad fit line NUMBER
command = \...#1#2
numbercommand = \...#1
textcommand = \...#1
deepnumbercommand = \...#1
deeptextcommand = \...#1
prefix = + - TEXT
placehead = yes no empty
incrementnumber = yes no LIST FILE
resetnumber = yes no
file = IDENTIFIER
expansion = yes no command
margintext = yes no
inherits from \setupheads

`\setupheader [.1.] [...2,...]`

1 TEXT margin edge OPTIONAL
2 state = normal stop start empty high none nomarking IDENTIFIER
strut = yes no
style = normal bold slanted boldslanted type cap small... COMMAND
leftstyle = normal bold slanted boldslanted type cap small... COMMAND
rightstyle = normal bold slanted boldslanted type cap small... COMMAND
leftwidth = DIMENSION
rightwidth = DIMENSION
before = COMMAND
after = COMMAND

`\setupheadertexts [.1.] [.2.] [.3.]`

1 text margin edge OPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber

`\setupheadnumber [.1.] [.2.]`

1 SECTION
2 NUMBER +cd:number -cd:number

`\setupheads [...*,...]`

* sectionnumber = yes NUMBER no
alternative = normal margin middle TEXT paragraph
separator = TEXT
stopper = TEXT
align = inner outer left right flushleft flushright middle center normal no yes
alightitle = yes float no
tolerance = verystRICT strict tolerant verytolerant stretch
indentnext = yes no
command = \...#1#2
margin = DIMENSION

`\setupheadtext [.1.] [...2,...]`

1 nl fr en uk de OPTIONAL
2 IDENTIFIER = TEXT

`\setuphyphenmark [...*,...]`

* sign = -- --- - ~ () = /

`\setupindentations [...,1...] [...,2...]`

1 IDENTIFIER OPTIONAL
2 style = normal bold slanted boldslanted type cap small... COMMAND
headstyle = normal bold slanted boldslanted type cap small... COMMAND
width = fit DIMENSION
text = TEXT
sample = TEXT
before = COMMAND
after = COMMAND
distance = DIMENSION
separator = TEXT

`\setupindenting [...,*...]`

* never none not no yes always first next small medium big normal odd even DIMENSION

`\setupinmargin [...,1...] [...,2...]`

1 left right NUMBER OPTIONAL
2 location = left right both
style = normal bold slanted boldslanted type cap small... COMMAND
before = COMMAND
after = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
line = NUMBER
distance = DIMENSION
separator = TEXT
width = DIMENSION
distance = DIMENSION
stack = yes no
inherits from \setupframed

`\setupinteraction [...,*...]`

* state = start stop
menu = on off
page = yes no
click = yes no
split = yes no
display = new
openaction = REFERENCE
closeaction = REFERENCE
openpageaction = REFERENCE
closepageaction = REFERENCE
calculate = IDENTIFIER
strut = yes no
width = DIMENSION
height = DIMENSION
depth = DIMENSION
style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
contrastcolor = IDENTIFIER
symbolset = IDENTIFIER
title = TEXT
subtitle = TEXT
author = TEXT
date = TEXT
keyword = TEXT
fieldlayer = auto IDENTIFIER

`\setupinteractionbar [...,*...]`

* state = start stop
alternative = a b c d e f g
symbol = yes no
width = DIMENSION height fit
height = DIMENSION height fit
depth = DIMENSION
color = IDENTIFIER
step = NUMBER small medium big
inherits from \setupframed

`\setupinteractionmenu [...1;...] [...,2.,...]`

1 IDENTIFIER
2 before = COMMAND
after = COMMAND
inbetween = COMMAND
left = COMMAND
right = COMMAND
middle = COMMAND
state = start stop none local
style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
contrastcolor = IDENTIFIER
distance = overlay DIMENSION
samepage = yes empty no none
unknownreference = yes empty no none
leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
position = yes no
inherits from \setupframed

`\setupinteractionscreen [...,*.,...]`

* width = DIMENSION fit max
height = DIMENSION fit max
backspace = DIMENSION
topspace = DIMENSION
horoffset = DIMENSION
veroffset = DIMENSION
option = max fit doublesided singlesided auto none bookmark
delay = NUMBER none

`\setupinterlinespace [...,*.,...]`

* height = NUMBER
depth = NUMBER
line = DIMENSION
top = NUMBER
bottom = NUMBER

`\setupinterlinespace [...*.]`

* reset small medium auto big on off

`\setupitemgroup [...1.] [...2.] [...,3.,...] [...,4.,...]`

1 IDENTIFIER OPTIONAL OPTIONAL OPTIONAL
2 NUMBER each
3 standard broad serried packed unpacked nowhite before after stopper joinedup atmargin inmargint autointro loose
repeat SECTION paragraph intext random reverse
4 margin = no standard DIMENSION
leftmargin = no standard DIMENSION
rightmargin = no standard DIMENSION
width = DIMENSION
distance = DIMENSION
step = DIMENSION
factor = NUMBER
items = NUMBER
start = NUMBER
before = COMMAND
inbetween = COMMAND
after = COMMAND
left = TEXT
right = TEXT
beforehead = COMMAND
afterhead = COMMAND
headstyle = normal bold slanted boldslanted type cap small... COMMAND
marstyle = normal bold slanted boldslanted type cap small... COMMAND
symstyle = normal bold slanted boldslanted type cap small... COMMAND
stopper = TEXT
n = NUMBER
symbol = NUMBER
align = inner outer left right flushleft flushright middle center normal no yes
symalign = left right flushleft flushright middle center
indentnext = yes no
textdistance = none big medium small

```

\setupitems [.,.*.,..]
* location = left right inmargin top bottom
  symbol = 1 2 ... n a ... TEXT none
  width = DIMENSION
  n = NUMBER unknown
  before = COMMAND
  inbetween = COMMAND
  align = inner outer left right flushleft flushright middle center normal no yes
  after = COMMAND

```

```

\setuplabeltext [.1.] [.2.]
1 nl fr en uk de es es OPTIONAL
2 IDENTIFIER = TEXT

```

```

\setuplanguage [.1.] [.,.2.,..]
1 nl fr en uk de es cz ..
2 inherits from \installlanguage

```

```

\setuplayout [.,.*.,..]
* width = DIMENSION fit middle
  height = DIMENSION fit middle
  backspace = DIMENSION
  topspace = DIMENSION
  margin = DIMENSION
  leftmargin = DIMENSION
  rightmargin = DIMENSION
  header = DIMENSION
  footer = DIMENSION
  top = DIMENSION
  bottom = DIMENSION
  leftedge = DIMENSION
  rightedge = DIMENSION
  headerdistance = DIMENSION
  footerdistance = DIMENSION
  topdistance = DIMENSION
  bottomdistance = DIMENSION
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  leftedgedistance = DIMENSION
  rightedgedistance = DIMENSION
  horoffset = DIMENSION
  veroffset = DIMENSION
  style = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  marking = on off color screen TEXT page
  location = left middle right bottom top singlesided doublesided
  scale = DIMENSION
  nx = NUMBER
  ny = NUMBER
  dx = DIMENSION
  dy = DIMENSION
  lines = NUMBER
  columns = NUMBER
  columndistance = DIMENSION
  grid = yes no
  bottomspace = DIMENSION
  cutspace = DIMENSION
  textdistance = DIMENSION
  textwidth = NUMBER
  textmargin = DIMENSION
  clipoffset = DIMENSION
  page = IDENTIFIER
  paper = IDENTIFIER

```

```

\setuplegend [.,.*.,..]
* n = NUMBER
  distance = DIMENSION
  inbetween = COMMAND
  width = DIMENSION
  height = DIMENSION
  location = right bottom
  bodyfont = 5pt ... 12pt small big

```

`\setuplinenumbering [..,*.,..]`

* conversion = numbers characters Characters romannumerals Romannumerals TEXT
start = NUMBER
step = NUMBER
width = DIMENSION
location = intext inmargin
style = normal bold slanted boldslanted type cap small... COMMAND
prefix = TEXT
referencing = on off

`\setuplines [..,*.,..]`

* before = COMMAND
after = COMMAND
inbetween = COMMAND
indenting = never none not no yes always first next small medium big normal odd even DIMENSION
space = yes no
option = packed

`\setuplinewidth [.*.]`

* DIMENSION

`\setuplist [...,1...] [...,2.,...]`

1 IDENTIFIER
2 state = start stop
alternative = a b c ... none command
coupling = on off
criterium = SECTION local previous current here intro all
pageboundaries = LIST
style = normal bold slanted boldslanted type cap small... COMMAND
numberstyle = normal bold slanted boldslanted type cap small... COMMAND
textstyle = normal bold slanted boldslanted type cap small... COMMAND
pagestyle = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
command = \...#1#2#3
numbercommand = \...#1
textcommand = \...#1
pagecommand = \...#1
interaction = cd:sectionnumber TEXT pagenumber all
before = COMMAND
after = COMMAND
inbetween = COMMAND
left = TEXT
right = TEXT
label = yes no
prefix = yes no none
pagenumber = yes no
headnumber = yes no
cd:sectionnumber = yes no
aligntitle = yes no
margin = DIMENSION
width = DIMENSION fit
height = DIMENSION fit broad
depth = DIMENSION fit broad
distance = DIMENSION
separator = TEXT
stopper = TEXT
symbol = none 1 2 3 ...
expansion = yes no command
maxwidth = DIMENSION
inherits from \setupframed

`\setuplistalternative [.*.] [...,2.,...]`

1 a b c
2 command = COMMAND
width = DIMENSION
stretch = DIMENSION
distance = DIMENSION

`\setupmakeup [1.] [2.,..]`

1 IDENTIFIER
2 width = DIMENSION
height = DIMENSION
voffset = DIMENSION
hoffset = DIMENSION
page = left yes right
commands = COMMAND
doublesided = yes no empty
headerstate = normal stop start empty none nomarking
footerstate = normal stop start empty none nomarking
textstate = normal stop start empty none nomarking
topstate = stop start
bottomstate = stop start
pagestate = stop start
color = IDENTIFIER

`\setupmarginblocks [..,*.,..]`

* location = inmargin left middle right
style = normal bold slanted boldslanted type cap small... COMMAND
width = DIMENSION
align = inner outer left right flushleft flushright middle center normal no yes
top = COMMAND
inbetween = COMMAND
bottom = COMMAND
left = COMMAND
right = COMMAND
before = COMMAND
after = COMMAND

`\setupmarginrules [.*.]`

* level = NUMBER
rulethickness = DIMENSION

`\setupmarking [1.] [2.,..]`

1 IDENTIFIER
2 state = start stop
separator = COMMAND
expansion = yes no

`\setupnarrower [..,*.,..]`

* left = DIMENSION
right = DIMENSION
middle = DIMENSION

`\setupnumbering [..,*.,..]`

* way = bytext bycd:section
state = start stop

`\setupoppositeplacing [.*.]`

* state = start stop
before = COMMAND
inbetween = COMMAND
after = COMMAND

`\setupoutput [...*,...]`

* IDENTIFIER

`\setuppagenumber [..,*.,..]`

* number = NUMBER
state = start stop keep

```

\setuppagenumbering [.,.*.,..]
* alternative = singlesided doublesided
  location   = header footer left right middle margin marginedge inleft inright
  conversion = numbers characters Characters romannumerals Romannumerals
  style      = normal bold slanted boldslanted type cap small... COMMAND
  left      = TEXT
  right     = TEXT
  way       = bytext bycd:section
  text      = TEXT
  numberseparator = TEXT
  textseparator = TEXT
  cd:sectionnumber = yes no
  separator   = TEXT
  strut       = yes no
  state       = start stop
  width       = DIMENSION
  command     = \...#1
  page        = last yes no

```

```

\setuppagetransitions [...*...]
* reset NUMBER OPTIONAL

```

```

\setuppalet [.*]
* IDENTIFIER

```

```

\setuppaper [.,.*.,..]
* paper = IDENTIFIER
  page  = IDENTIFIER
  nx    = NUMBER
  ny    = NUMBER
  width = DIMENSION
  height = DIMENSION
  topspace = DIMENSION
  backspace = DIMENSION
  option = max fit
  method = normal IDENTIFIER

```

```

\setuppapersize [...1...] [...2...]
1 A3 A4 A5 A6 letter ... CD IDENTIFIER LANDSCAPE mirrored rotated 90 180 270
2 negative inherits from \setuppapersize

```

```

\setupparagraphnumbering [.,.*.,..]
* state = start stop reset line
  style = normal bold slanted boldslanted type cap small... COMMAND
  distance = DIMENSION

```

```

\setupparagraphs [.1.] [.2.] [...,3.,..]
1 IDENTIFIER OPTIONAL
2 NUMBER each
3 style = normal bold slanted boldslanted type cap small... COMMAND
  width = DIMENSION
  height = DIMENSION
  align = inner outer left right flushleft flushright middle center normal no yes
  tolerance = verystrict strict tolerant verytolerant stretch
  distance = DIMENSION
  before = COMMAND
  after = COMMAND
  inner = COMMAND
  command = COMMAND
  rule = on off

```

```

\setuppositioning [.,.*.,..]
* state = start overlay
  unit = cm pt em mm ex es in
  factor = NUMBER
  scale = NUMBER
  offset = yes no
  xstep = absolute relative
  ystep = absolute relative

```

```
\setupprofiles [..,*.,..]  
* option = test
```

```
\setupprograms [..,*.,..]  
* directory = TEXT
```

```
\setuppublications [..,*.,..]  
* alternative = apa normal  
  inherits from \setupenumerations
```

```
\setupquote [..,*.,..]  
* before = COMMAND  
  after = COMMAND  
  style = normal bold slanted boldslanted type cap small... COMMAND  
  color = IDENTIFIER  
  location = TEXT margin
```

```
\setupreferencelist [1.] [..,2.,..]  
1 IDENTIFIER OPTIONAL  
2 state = start stop  
  criterium = SECTION local previous all  
  command = COMMAND  
  before = COMMAND  
  after = COMMAND
```

```
\setupreferencing [..,*.,..]  
* state = start stop  
  cd:sectionnumber = yes no  
  prefix = + - TEXT  
  interaction = label TEXT all symbol  
  width = DIMENSION  
  left = COMMAND  
  right = COMMAND  
  convertfile = yes no small big  
  separator = TEXT  
  autofile = yes no page  
  global = yes no  
  export = yes no
```

```
\setupregister [1.] [2.] [..,3.,..]  
1 SINGULAR NAME OPTIONAL  
2 IDENTIFIER  
3 n = NUMBER  
  balance = yes no  
  align = inner outer left right flushleft flushright middle center normal no yes  
  style = normal bold slanted boldslanted type cap small... COMMAND  
  pagestyle = normal bold slanted boldslanted type cap small... COMMAND  
  textstyle = normal bold slanted boldslanted type cap small... COMMAND  
  indicator = yes no  
  coupling = yes no  
  cd:sectionnumber = yes no  
  criterium = SECTION local all  
  distance = DIMENSION  
  symbol = 1 2 ... n a ... none  
  interaction = pagenumber TEXT  
  expansion = yes no command  
  referencing = on off  
  command = \...#1  
  location = left middle right  
  maxwidth = DIMENSION  
  unknownreference = empty none  
  alternative = a b A B  
  prefix = both first none  
  compress = no yes  
  deeptextcommand = \...#1
```

```
\setuprotate [..,*.,..]  
* rotation = NUMBER  
  location = normal high fit broad depth  
  inherits from \setupframed
```

```
\setupscreens [.,.*.,..]
* method = dot rule external
  resolution = NUMBER
  factor = NUMBER
  screen = NUMBER
```

```
\setupsection [.1.] [.2.] [.,.3.,..]
1 IDENTIFIER OPTIONAL
2 IDENTIFIER
3 conversion = numbers characters Characters romannumerals Romannumerals
  previousnumber = yes no
```

```
\setupsectionblock [.1.] [.,.2.,..]
1 IDENTIFIER
2 number = yes no
  page = yes right
  before = COMMAND
  after = COMMAND
```

```
\setupsorting [.1.] [.,.2.,..]
1 IDENTIFIER
2 before = COMMAND
  after = COMMAND
  command = \...#1
  state = start stop
  criterium = all used
  style = normal bold slanted boldslanted type cap small... COMMAND
  expansion = yes no command
```

```
\setupspacing [.*.]
* broad packed
```

```
\setupstrut [.*.]
* yes no cap TEXT
```

```
\setupsubpagenumber [.,.*.,..]
* way = bytext bycd:section
  state = start stop none
```

```
\setupsymbolset [.*.]
* IDENTIFIER
```

```
\setupsynchronization [.,.*.,..]
* state = start stop
```

```
\setupsynchronizationbar [.,.*.,..]
* alternative = page local
  width = DIMENSION height fit
  height = DIMENSION
  style = normal bold slanted boldslanted type cap small... COMMAND
  color = IDENTIFIER
  inherits from \setupframed
```

```
\setupsynonyms [.1.] [.,.2.,..]
1 IDENTIFIER
2 textstyle = normal bold slanted boldslanted type cap small... COMMAND
  synonymstyle = normal bold slanted boldslanted type cap small... COMMAND
  location = left right top serried inmargin inleft inright
  width = DIMENSION
  state = start stop
  criterium = all used
  conversion = yes no
  expansion = yes no command
  command = \...#1#2#3
```

```
\setupssystem [.,.,*.,..]
* resolution = NUMBER
  file       = TEXT
  directory  = TEXT
  random     = normal small medium big NUMBER
```

```
\setupstab [.,.,*.,..]
* sample     = TEXT
  width      = DIMENSION
  headstyle  = normal bold slanted boldslanted type cap small... COMMAND
  location   = left right
```

```
\setuptables [.,.,*.,..]
* distance   = small medium big
  bodyfont   = 5pt ... 12pt small big
  HL         = NUMBER small medium big none
  VL         = NUMBER small medium big none
  depth      = NUMBER strut
  height     = NUMBER strut
  rulethickness = DIMENSION
  rulecolor  = IDENTIFIER
  align      = inner outer left right flushleft flushright middle center normal no yes
  commands  = COMMAND
  align      = inner outer left right flushleft flushright middle center normal no yes
  background = screen color none
  backgroundscreen = NUMBER
  backgroundcolor = IDENTIFIER
  bodyfont   = 5pt ... 12pt small big
```

```
\setuptabulate [1.] [.,.,2.,..]
1 IDENTIFIER OPTIONAL
2 unit = DIMENSION
  indenting = never none not no yes always first next small medium big normal odd even DIMENSION
  before    = COMMAND
  after     = COMMAND
  inner     = COMMAND
  EQ        = TEXT
  rulecolor = IDENTIFIER
  align     = inner outer left right flushleft flushright middle center normal no yes
  rulethickness = DIMENSION
  distance  = blank grid depth DIMENSION small medium big none
  bodyfont  = 5pt ... 12pt small big
  rule      = normal line
  split     = yes no
```

```
\setuptext [1.] [.,.,2.,..]
1 inherits from from \setupheader
2 inherits from \setupheader
```

```
\setuptextrules [.,.,*.,..]
* location = left inmargin
  before   = COMMAND
  after    = COMMAND
  inbetween = COMMAND
  width    = DIMENSION
  distance = DIMENSION
  bodyfont = 5pt ... 12pt small big
  color    = IDENTIFIER
  style    = normal bold slanted boldslanted type cap small... COMMAND
  rulecolor = IDENTIFIER
```

```
\setuptexttexts [1.] [2.] [3.]
1 text margin edge OPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber
```

```

\setupthinrules [.*.]
* interlinespace = small medium big
  n              = NUMBER
  before         = COMMAND
  inbetween      = COMMAND
  after          = COMMAND
  color          = IDENTIFIER
  backgroundcolor = IDENTIFIER
  height         = DIMENSION max
  depth          = DIMENSION max
  alternative    = a b c d
  rulethickness  = DIMENSION
  color          = IDENTIFIER
  background     = color
  backgroundcolor = IDENTIFIER

```

```

\setuptolerance [...,*...]
* horizontal vertical stretch space verystrict strict tolerant verytolerant

```

```

\setuptop [.1.] [...,.2.,...]
1 inherits from \setupheader
2 inherits from \setupheader

```

```

\setuptoptexts [.1.] [.2.] [.3.]
1 text margin edgeOPTIONAL
2 TEXT SECTION date MARK pagenumber
3 TEXT SECTION date MARK pagenumber

```

```

\setuptype [...,*...,...]
* space = on off
  option = slanted normal none
  style  = normal bold slanted boldslanted type cap small... COMMAND
  color  = IDENTIFIER

```

```

\setuptyping [.1.] [...,.2.,...]
1 file typing IDENTIFIER
2 space = on off
  page  = yes no
  option = slanted normal commands color none
  text  = yes no
  icommand = COMMAND
  vcommand = COMMAND
  ccommand = COMMAND
  before  = COMMAND
  after   = COMMAND
  margin  = DIMENSION standard yes no
  evenmargin = DIMENSION
  oddmargin = DIMENSION
  blank   = DIMENSION small medium big standard halflineline
  escape  = TEXT
  space   = on off
  tab     = NUMBER yes no
  page    = yes no
  indentnext = yes no
  style   = normal bold slanted boldslanted type cap small... COMMAND
  color   = IDENTIFIER
  palet   = IDENTIFIER
  lines   = yes no hyphenated
  empty   = yes all no
  numbering = line file no
  bodyfont = 5pt ... 12pt small big
  strip   = no auto NUMBER

```

```

\setupunderbar [...,*...,...]
* alternative = a b c
  rulethickness = DIMENSION
  bottomoffset = DIMENSION
  topoffset    = DIMENSION
  rulecolor    = IDENTIFIER

```

```
\setupurl [..,.*,..]
* style = normal bold slanted boldslanted type cap small... COMMAND
  urlalternative = none both before after
  urlspace = yes no
```

```
\setupversions [..,.*,..]
* number = NUMBER
  style = normal bold slanted boldslanted type cap small... COMMAND
```

```
\setupwhitespace [.*]
* none small medium bigoline fixed fix DIMENSION
```

```
\showbodyfont [...;*..]
* inherits from \setupbodyfont
```

```
\showbodyfontenvironment [...;*..]
* inherits from \setupbodyfont OPTIONAL
```

```
\showcolor [.*]
* IDENTIFIER
```

```
\showcolorgroup [.*] [...;*..]
1 IDENTIFIER
2 horizontal vertical name value NUMBER
```

```
\showexternalfigures [..,.*,..]
* alternative = a b c OPTIONAL
```

```
\showfields [...;*..]
* IDENTIFIER OPTIONAL
```

```
\showframe [.*]
* TEXT marginPage
```

```
\showgrid [...;*..] {...}
1 reset top bottom none all lines frame nonumber right left outer
2 CONTENT
```

```
\showlayout
```

```
\showmakeup
```

```
\showpalet [.*] [...;*..]
1 IDENTIFIER
2 horizontal vertical name value
```

```
\showprint [...;*..] [...;*..] [...;*..]
1 inherits from \setuppapersize
2 inherits from \setuppapersize
3 inherits from \setuplayout
```

```
\showsetups
```

```
\showstruts
```

```
\showsymbolset [.*]
* IDENTIFIER
```

`\somedline [...]`
* REFERENCE

`\somedhere {.^.^} [.^.^]`
1 CONTENT
2 CONTENT
3 REFERENCE

`\sort [.^.^] {.^.^}`
1 TEXT
2 CONTENT

`\space`

`\splitfloat [...,1...] {.^.^} {.^.^}`
1 inherits from `\splitfloat`
2 CONTENT
3 CONTENT

`\startregister [.^.^] {.^.^+.^.^+.^.^}`
1 TEXT
2 INDEX

`\stretched {.*}`
* WORD

`\sub [...,*...]`
* REFERENCE

`\subject [...,1...] {.^.^}`
1 REFERENCE OPTIONAL
2 CONTENT

`\subsection [...,1...] {.^.^}`
1 REFERENCE OPTIONAL
2 CONTENT

`\subsubject [...,1...] {.^.^}`
1 REFERENCE OPTIONAL
2 CONTENT

`\subsubsection [...,1...] {.^.^}`
1 REFERENCE OPTIONAL
2 CONTENT

`\subsubsubject [...,1...] {.^.^}`
1 REFERENCE OPTIONAL
2 CONTENT

`\switchtobodyfont [...,*...]`
* IDENTIFIER serif regular roman sans support sansserif mono teletype handwritten calligraphic 5pt ... 12pt
small big

`\sym {.*}`
* CONTENT

`\symbol [.^.^] [.^.^]`
1 IDENTIFIER
2 IDENTIFIER

`\startsymbolset [...]` ... `\stop`
* IDENTIFIER

`\startsynchynchronization ... \stop`

`\synchronizationbar [1.] [...,2.,...]`
1 IDENTIFIER
2 alternative = page local
inherits from \setupsynchronizationbar

`\synchronize`

`\synonym [1.] {2.} {3.}`
1 TEXT OPTIONAL
2 CONTENT
3 CONTENT

`\tab {1.} 2.`
1 CONTENT
2 NOTHING

`\starttable [...]` ... `\stop`
* TEXT IDENTIFIER

`\starttables [...]` ... `\stop`
* TEXT IDENTIFIER

`\starttabulate [1.] [...,2.,...]` ... `\stoptabulate`
1 TEXT OPTIONAL OPTIONAL
2 *inherits from \setuexternalfigures*

`\tex {1.}`
* CONTENT

`\textreference [1.] {2.}`
1 REFERENCE
2 CONTENT

`\textrule [1.] {2.}`
1 top bottom OPTIONAL OPTIONAL
2 CONTENT

`\thinrule`

`\thinrules [1.]`
* *inherits from \setupthinrules*

`\title [...,1,...] {2.}`
1 REFERENCE OPTIONAL
2 CONTENT

`\tooltip [1.] {2.} {3.}`
1 left right middle
2 CONTENT
3 CONTENT

`\translate [...,*,...]`
* IDENTIFIER = TEXT

```
\typ {...}
* CONTENT
```

```
\type {...}
* CONTENT
```

```
\typebuffer [...]
* IDENTIFIER
```

```
\typefile [...] {...}
1 IDENTIFIEROPTIONAL
2 CONTENT
```

```
\starttyping ... \stoptyping
```

```
\underbar {...}
* CONTENT
```

```
\underbars {...*...}
* WORD
```

```
\startunpacked ... \stop
```

```
\useblocks [...1,...] [...2,...]
1 IDENTIFIER OPTIONAL
2 IDENTIFIER
```

```
\usecommands {...}
* CONTENT
```

```
\usedirectory [...*,...]
* IDENTIFIER reset
```

```
\useencoding [...*,...]
* IDENTIFIER
```

```
\useexternaldocument [...1] [...2] [...3]
1 IDENTIFIER
2 file
3 TEXT
```

```
\useexternalfigure [...1] [...2] [...3] [...4,...,...]
1 IDENTIFIER OPTIONAL OPTIONAL OPTIONAL
2 FILE
3 IDENTIFIER
4 inherits from \setupexternalfigures
```

```
\useexternalfile [...1] [...2] [...3] [...4,...,...]
1 IDENTIFIER
2 IDENTIFIER
3 FILE
4 bodyfont = 5pt ... 12pt small big
```

```
\useexternalfiles [...1] [...2,...,...]
1 IDENTIFIER
2 bodyfont = 5pt ... 12pt small big
file = FILE
```

\useexternalsoundtrack [..¹.] [..².]

1 IDENTIFIER
2 FILE

\usemodule [...,*...]

* IDENTIFIER

\userferences [...,*...]

* FILE

\usespecials [...,*...]

* reset IDENTIFIER

\usesymbols [...*...]

* IDENTIFIER

\usetypescript [...¹;...] [...²;...] [...³;...]

1 IDENTIFIER OPTIONAL OPTIONAL
2 IDENTIFIER
3 IDENTIFIER

\usetypescriptfile [...,*...]

* FILE

\useURL [..¹.] [..².] [..³.] [..⁴.]

1 IDENTIFIER
2 TEXT
3 file
4 TEXT

\version [...*...]

* final concept temporary

\v1 [...*...]

* NUMBER

\weekday {...*...}

* CONTENT

\WEEKDAY {...*...}

* CONTENT

\whitespace

\WORD {...*...}

* WORD

\Word {...*...}

* WORD

\wordright {...*...}

* CONTENT

\Words {...*... ..}

* WORD

```
\WORDS {...*...}
* WORD
```

```
\writebetweenlist [1.] {2.}
1 SECTION IDENTIFIER
2 CONTENT
```

```
\writetolist [1.] {2.} {3.}
1 SECTION IDENTIFIER
2 CONTENT
3 CONTENT
```

```
\writetoreferencelist [1.] {2.} {3.}
1 IDENTIFIER
2 CONTENT
3 CONTENT
```

```
\writetoregister [1.] [2.] {...3+...}
1 SINGULAR NAME          OPTIONAL
2 TEXT
3 INDEX
```


The background consists of a complex, layered pattern of overlapping, rounded rectangular shapes. The shapes are outlined in various shades of green, from light to dark, and some are filled with a light grey color. The overall effect is a textured, geometric composition.

PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com