

The background features a light grey color with several overlapping, hand-drawn green lines and shapes. These include horizontal and vertical scribbles, as well as several rounded rectangular boxes of varying sizes and orientations, some of which are filled with a light grey color. The overall style is abstract and artistic.

ConTeXt

commands

EN

ConTeXt

commands

en / english
June 14, 2009

`\about {.1.} [.2.]`

- 1 TEXT
- 2 REFERENCE

`\adaptlayout [...1;.2.] [...,.2.,...]`
OPTIONAL

- 1 NUMBER
- 2 `height = DIMENSION max`
`lines = NUMBER`

`\appendix [...1;.2.] {.2.}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\at {.1.} {.2.} [.3.]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\atpage [.*]`

- * REFERENCE

`\background {.*}`

- * TEXT

`\blackrule [...,.*,...]`
OPTIONAL

- * *inherits from* `\setupblackrules`

`\blackrules [...,.*,...]`

- * *inherits from* `\setupblackrules`

`\blank [...,.*,...]`
OPTIONAL

- * `small medium big nowhite back white disable force reset line halfline FORMULA fixed flexible none`
`always outer joinedup`

`\bookmark [.1.] {.2.}`
OPTIONAL

- 1 IDENTIFIER
- 2 TEXT

`\but [.*]`

- * REFERENCE

`\button [..,1,...] {2.} [...3,...]`
OPTIONAL

- 1 *inherits from* \setupbuttons
- 2 TEXT
- 3 REFERENCE

`\bypassblocks [...1,...] [...2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\cap {.*}`

- * TEXT

`\CAP {.*}`

- * TEXT

`\Cap {.*}`

- * TEXT

`\Caps {.. .* ..}`

- * WORD

`\chapter [...1,...] {2.}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\Character {.*}`

- * TEXT

`\character {.*}`

- * TEXT

`\characters {.*}`

- * TEXT

`\Characters {.*}`

- * TEXT

`\chem {1.} {2.} {3.}`

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\clip [...,1,...] {2.}`
OPTIONAL

- 1 *inherits from* \setupclipping
- 2 TEXT

`\clonefield [1.] [...2,...] [...3,...] [...4,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 IDENTIFIER
- 4 IDENTIFIER

`\color [1.] {2.}`

- 1 TEXT
- 2 TEXT

`\column`

`\comment [1.] [...,2,...] {3.}`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcomment
- 3 TEXT

`\comparecolorgroup [...]`

- * IDENTIFIER

`\comparepalet [...]`

- * IDENTIFIER

`\completeCOMBINEDLIST [1.] [...,2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcombinedlist

`\completelistofFLOATS`

`\completelistofSORTS`

`\completelistofSYNONYMS`

`\currentdate [...;*...]`

* *inherits from* \date

`\currentheadnumber`

`\date [...;.1.;...]` `[...;.2.;...]`
 OPTIONAL OPTIONAL

1 d = NUMBER
m = NUMBER
y = NUMBER

2 day month year weekday d m y w dd mm yy space -- day+ d+ dd+ referral TEXT

`\decouplemarking [.*.]`

* IDENTIFIER

`\define [.1.] \.2. {.3.}`
 OPTIONAL

1 NUMBER
2 NAME
3 TEXT

`\defineblank [.1.] [.2.]`

1 IDENTIFIER
2 *inherits from* \setupblank

`\defineblock [.*.]`

* IDENTIFIER

`\definebodyfont [...;.1.;...]` `[...;.2.;...]` `[...;.3.;...]`
 OPTIONAL

1 5pt ... 12pt small big
2 rm ss tt hw cg mm
3 tf = FILE
bf = FILE
sl = FILE
it = FILE
bs = FILE
bi = FILE
sc = FILE
mr = FILE
ex = FILE
mi = FILE
sy = FILE
ma = FILE
mb = FILE
mc = FILE
md = FILE

`\definebodyfont [.1.] [.2.] [.3.]`

1 IDENTIFIER
2 *inherits from* \setupbodyfont
3 *inherits from* \setupbodyfont

```

\definebodyfontenvironment [.1.] [.2.] [...,3,...]
                        OPTIONAL          OPTIONAL

1  IDENTIFIER
2  5pt ... 12pt default
3  text          = DIMENSION
    script       = DIMENSION
    scriptscript = DIMENSION
    x            = DIMENSION
    xx           = DIMENSION
    a            = DIMENSION
    b            = DIMENSION
    c            = DIMENSION
    d            = DIMENSION
    small        = DIMENSION
    big          = DIMENSION
    interlinespace = DIMENSION
    em           = normal bold slanted boldslanted type cap small... COMMAND

```

```

\definebodyfont [.1.] [.2.] [.3.]

```

```

1  inherits from \setupbodyfont
2  inherits from \setupbodyfont
3  IDENTIFIER

```

```

\definebuffer [...*]

```

```

*  IDENTIFIER

```

```

\definecolor [.1.] [...,2,...]

```

```

1  IDENTIFIER
2  r = TEXT
    g = TEXT
    b = TEXT
    c = TEXT
    m = TEXT
    y = TEXT
    k = TEXT
    s = TEXT
    h = TEXT
    t = TEXT
    a = TEXT
    p = TEXT
    e = TEXT

```

```

\definecolorgroup [.1.] [.2.] [x:y:3=,...]
                        OPTIONAL

```

```

1  IDENTIFIER
2  rgb cmyk gray s
3  TRIPLET

```

```

\definecombinedlist [.1.] [...2,...] [...,3,...]
                        OPTIONAL

```

```

1  IDENTIFIER
2  LIST
3  inherits from \setupcombinedlist

```

```

\defineconversion [.1.] [.2.]

```

```

1  IDENTIFIER
2  COMMAND TEXT

```


`\definefontfeature` [¹.] [².] [³.]

OPTIONAL

1 TEXT
2 IDENTIFIER
3 `compose` = no `yes`
`mode` = `node` base
`tlig` = no `yes`
`trep` = no `yes`
`script` = IDENTIFIER
`language` = IDENTIFIER
`..tag..` = no `yes`

`\definefonthandling` [¹.] [².] [³.]

1 IDENTIFIER
2 IDENTIFIER
3 `type` = hanging `hz` `spacing` `tag`
`right` = NUMBER
`left` = NUMBER
`factor` = NUMBER
`min` = NUMBER
`max` = NUMBER
`step` = NUMBER

`\definefontsynonym` [¹.] [².] [³.]

OPTIONAL

1 TEXT
2 IDENTIFIER
3 `encoding` = IDENTIFIER
`features` = IDENTIFIER
`handling` = IDENTIFIER
`mapping` = IDENTIFIER

`\defineframed` [¹.] [².,.,.]

OPTIONAL

1 IDENTIFIER
2 *inherits from* `\setupframedtexts`

`\defineframedtext` [¹.] [².,.,.]

OPTIONAL

1 IDENTIFIER
2 *inherits from* `\setupframedtexts`

`\definehead` [¹.] [².]

1 IDENTIFIER
2 SECTION

`\defineindenting` [¹.] [².,.,.]

1 IDENTIFIER
2 *inherits from* `\setupindentations`

`\defineinteractionmenu` [...¹,...] [...².,.,.]

OPTIONAL

1 `left` `right` `top` `bottom` IDENTIFIER
2 *inherits from* `\setupinteractionmenu`

`\definepapersize [.1.] [...,2,...]`

1 IDENTIFIER
2 width = DIMENSION
height = DIMENSION
offset = DIMENSION
scale = NUMBER

`\defineparagraphs [.1.] [...,2,...]`

1 IDENTIFIER
2 n = NUMBER
rule = on off
height = fit DIMENSION
before = COMMAND
after = COMMAND
inner = COMMAND
distance = DIMENSION
tolerance = verystRICT strict tolerant verytolerant stretch
align = inner outer left right flushleft flushright middle center normal no yes

`\defineprofile [...1;...] [...2;...]`

1 IDENTIFIER
2 IDENTIFIER

`\defineprogram [.1.] [.2.] [.3.]`

1 IDENTIFIER
2 TEXT
3 TEXT

`\definereference [.1.] [...2,...]`

1 IDENTIFIER
2 REFERENCE

`\definereferenceformat [.1.] [...,2,...]`

1 IDENTIFIER
2 left = TEXT
right = TEXT
text = TEXT
label = IDENTIFIER

`\definereferencelist [.1.] [...,2,...]`
OPTIONAL

1 IDENTIFIER
2 *inherits from* \setupreferencelist

`\defineregister [.1.] [.2.]`

1 SINGULAR NAME
2 PLURAL NAME

`\definesection [..]`

* IDENTIFIER

`\definesectionblock [..] [.., 2, ..]`
OPTIONAL

1 *inherits from* \setupsectionblock
2 *inherits from* \setupsectionblock

`\definesorting [..] [..] [..]`
OPTIONAL

1 SINGULAR NAME
2 PLURAL NAME
3 COMMAND

`\definestartstop [..] [.., 2, ..]`

1 IDENTIFIER
2 before = COMMAND
after = COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
commands = COMMAND

`\definesubfield [..] [..] [.., 3, ..]`

1 IDENTIFIER
2 IDENTIFIER
3 IDENTIFIER

`\definesymbol [..] [..]`

1 IDENTIFIER
2 TEXT

`\definesynonyms [..] [..] [..] [..]`
OPTIONAL

1 SINGULAR NAME
2 PLURAL NAME
3 COMMAND
4 COMMAND

`\definetabletemplate [..] [..] [..] [..]`
OPTIONAL OPTIONAL

1 IDENTIFIER
2 TEXT
3 TEXT
4 TEXT

`\definetabulate [..] [..] [..]`
OPTIONAL

1 IDENTIFIER
2 IDENTIFIER
3 TEXT

```
\definetext [.1.] [.2.] [.3.] [.4.] [.5.]
                OPTIONAL OPTIONAL
```

- 1 IDENTIFIER
- 2 header footer
- 3 TEXT
- 4 TEXT
- 5 TEXT

```
\definetype [.1.] [...,2,...]
```

- 1 IDENTIFIER
- 2 *inherits from* \setuptype

```
\definetypface [.1.] [.2.] [.3.] [.4.] [.5.] [.6.]
                OPTIONAL OPTIONAL
```

- 1 TEXT
- 2 rm ss tt mm hw cg
- 3 IDENTIFIER
- 4 IDENTIFIER
- 5 IDENTIFIER
- 6 features = IDENTIFIER
rscale = NUMBER
encoding = IDENTIFIER
text = IDENTIFIER

```
\definetyping [.1.] [...,2,...]
```

- 1 *inherits from* \setuptyping
- 2 *inherits from* \setuptyping

```
\defineversion [.1.] [...2,...]
```

- 1 IDENTIFIER
- 2 NUMBER

```
\DESCRIPTION {.1.} .2.
```

- 1 TEXT
- 2 EMPTY

```
\determineheadnumber [...]
```

- * SECTION

```
\determinelistcharacteristics [...,1,...] [...,2,...]
                OPTIONAL
```

- 1 IDENTIFIER
- 2 *inherits from* \setuplist

```
\disableinteractionmenu [.1.] [...2,...]
```

- 1 left right top bottom IDENTIFIER
- 2 REFERENCE

`\emptylines [...]`

* NUMBER

`\ENUMERATION ...`

* EMPTY

`\externalfigure [1] [...,2,...]`
OPTIONAL

1 FILE

2 *inherits from* \setupexternalfigures

`\field [...]`

* IDENTIFIER

`\fieldstack [1] [...,2,...] [...,3,...]`
OPTIONAL OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

3 *inherits from* \setupfields

`\fillinfield [1] {2}`
OPTIONAL

1 TEXT

2 TEXT

`\fillinline [...,1,...] 2.`
OPTIONAL

1 *inherits from* \setupfillinlines

2 EMPTY

`\fillinrules [...,1,...] {2} {3}`
OPTIONAL OPTIONAL

1 *inherits from* \setupfillinrules

2 TEXT

3 TEXT

`\fillintext [...,1,...] {2} {3}`
OPTIONAL OPTIONAL

1 *inherits from* \setupfillinrules

2 TEXT

3 TEXT

`\fitfield [...]`

* IDENTIFIER

`\fixedspaces`

`\followprofile {..} [..]`

- 1 TEXT
- 2 TEXT

`\followprofileversion {..} [..] [..]`

- 1 TEXT
- 2 TEXT
- 3 IDENTIFIER

`\followversion {..} [..]`

- 1 TEXT
- 2 TEXT

`\footnote [..] {..}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\footnotetext [..] {..}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\forceblocks [...1;...] [...2;...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\fraction {..} {..}`

- 1 TEXT
- 2 TEXT

`\framed [..,1,...] {..}`
OPTIONAL

- 1 *inherits from \setupframed*
- 2 TEXT

`\FRAMEDTEXT [..,*,...]`
OPTIONAL

- * *inherits from \setupframedtexts*

`\from [..]`

- * REFERENCE

`\getbuffer [..]`
OPTIONAL

- * IDENTIFIER

`\getmarking [1.] [2.]`

- 1 IDENTIFIER
- 2 first last previous both all current

`\godown [...]`

- * DIMENSION

`\goto {1.} {2.} [...3,...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\gotobox {1.} [...2,...]`

- 1 TEXT
- 2 REFERENCE

`\graycolor [...]`

- * TEXT

`\grid [...,*,...]`

- * x = NUMBER
- y = NUMBER
- nx = NUMBER
- ny = NUMBER
- dx = NUMBER
- dy = NUMBER
- xstep = NUMBER
- ystep = NUMBER
- offset = yes no
- factor = NUMBER
- scale = NUMBER
- unit = cm pt em mm ex es in
- location = left middle

`\hairline`

`\head [...,*,...]`
OPTIONAL

- * REFERENCE

`\headnumber [...]`
OPTIONAL

- * SECTION

`\headtext {...}`

- * TEXT

`\hideblocks [...1...] [...2...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\high {...}`

- * TEXT

`\hl [...]`

- * NUMBER

`\in {.1.} {.2.} [...3.]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\INDENTATION ...`

- * EMPTY

`\indenting [...,*...]`

- * never none not no yes always first next small medium big normal odd even DIMENSION

`\inframed [...,1...] {...2.}`
OPTIONAL

- 1 inherits from \setupframed
- 2 TEXT

`\inner [...1.] [...2.] {...3.}`
OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\inleft [...1.] [...2.] {...3.}`
OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\inline [...]`

- * REFERENCE

`\inmargin [...1.] [...2.] {...3.}`
OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\inothermargin` [¹.] [².] {³.}

OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\inouter` [¹.] [².] {³.}

OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\inright` [¹.] [².] {³.}

OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\installlanguage` [¹.] [...,².,...]

- 1 IDENTIFIER
- 2 spacing = packed broad
lefthyphenmin = NUMBER
righthyphenmin = NUMBER
state = start stop
leftsentence = COMMAND
rightsentence = COMMAND
leftsubsentence = COMMAND
rightsubsentence = COMMAND
leftquote = COMMAND
rightquote = COMMAND
leftquotation = COMMAND
rightquotation = COMMAND
leftspeech = COMMAND
middlespeech = COMMAND
rightspeech = COMMAND
limittext = TEXT
date = TEXT
compoundhyphen = COMMAND
leftcompoundhyphen = COMMAND
rightcompoundhyphen = COMMAND
default = IDENTIFIER

`\interactionbar` [...,*.,...]

- * inherits from `\setupinteractionbar`

`\interactionbuttons` [...,¹.,...] [...,².,...]

OPTIONAL

- 1 inherits from `\setupinteractionbar`
- 2 IDENTIFIER

`\item` [...,*.,...]

OPTIONAL

- * REFERENCE

`\items` [...,¹.,...] {...².. ..}

OPTIONAL

- 1 inherits from `\setupitems`
- 2 TEXT

`\its [...,*...]`
OPTIONAL

* REFERENCE

`\keepblocks [...1...] [...2...]`
OPTIONAL

1 IDENTIFIER

2 all IDENTIFIER

`\LABELING [...]`
OPTIONAL

* REFERENCE

`\labels [...]`

* IDENTIFIER

`\labeltext {...}`

* TEXT

`\language [...]`

* nl fr en uk de es cz ..

`\leftaligned {...}`

* TEXT

`\listsymbol [...1] {...2}`

1 IDENTIFIER

2 TEXT

`\loadSORTS`

`\loadSYNONYMS`

`\logfields`

`\lohi [...1] {...2} {...3}`
OPTIONAL

1 low

2 TEXT

3 TEXT

`\low {...}`

* TEXT

`\mainlanguage [...]`

* nl fr en uk de es cz ..

`\mapfontsize [..] [..]`

1 DIMENSION

2 DIMENSION

`\mar [...1,...] {..2}`
OPTIONAL

1 REFERENCE

2 TEXT

`\marginrule [..] {..}`

1 NUMBER

2 TEXT

`\margintext [..] [..] {..}`
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\marking [..] {..}`

1 IDENTIFIER

2 TEXT

`\markversion`

`\mathematics {...}`

* TEXT

`\mediaeval {...}`

* TEXT

`\midaligned {...}`

* TEXT

`\mirror {...}`

* TEXT

`\MONTH {...}`

* TEXT

`\month {...}`

* TEXT

`\moveongrid [...;...]`

OPTIONAL

* standard top both bottom -top -both -bottom TEXT high middle low page broad fit depth line reset
none DIMENSION

`\name {...}`

* TEXT

`\nextSECTION`

`\nocap {...}`

* TEXT

`\noheaderandfooterlines`

`\noindenting`

`\nolist {...}`

* TEXT

`\nomarking {...}`

* TEXT

`\nomoreblocks`

`\nomorefiles`

`\nop`

`\nospace`

`\note [...]`

* REFERENCE

`\notopandbottomlines`

`\nowhitespace`

`\numbers {...}`

* TEXT

`\overbar {...}`

* TEXT

`\overbars {...*...}`

* WORD

`\overstrike {...}`

* TEXT

`\overstrikes {...*...}`

* WORD

`\packed`

`\page [...*...]`

* yes makeup no preference bigpreference left right disable last quadruple even odd blank empty reset
start stop

`\pagereference [...]`

* REFERENCE

`\pagetype [...]`

* IDENTIFIER

`\PARAGRAPH`

`\part [...1...]{...2}`

OPTIONAL

1 REFERENCE

2 TEXT

`\periods [...]`

* NUMBER

`\placebookmarks [...1...][...2...]`

OPTIONAL

OPTIONAL

1 IDENTIFIER

2 IDENTIFIER all

`\placecombinedlist` [¹.] [OPTIONAL...².,...]

- 1 IDENTIFIER
- 2 *inherits from* \setupcombinedlist

`\placeCOMBINEDLIST` [¹.] [OPTIONAL...².,...]

- 1 IDENTIFIER
- 2 *inherits from* \setupcombinedlist

`\placeFLOAT` [OPTIONAL.¹.] [OPTIONAL...².,...] {³.} {⁴.}

- 1 left right here top bottom inleft inright inmargin margin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge inner outer line high low fit page leftpage rightpage opposite always auto force tall reset line height depth split 90 180 270
- 2 REFERENCE
- 3 TEXT
- 4 TEXT

`\placefootnotes` [OPTIONAL...^{*}.,...]

- * *inherits from* \setupfootnotes

`\placeformula` [OPTIONAL...¹.,...] {OPTIONAL.².} \$\$³.\$\$

- 1 REFERENCE
- 2 TEXT
- 3

`\placelegend` {¹.} {².}

- 1 TEXT
- 2 TEXT

`\placelist` [OPTIONAL...¹.,...] [OPTIONAL...².,...]

- 1 IDENTIFIER
- 2 *inherits from* \setuplist

`\placelistofFLOATS`

`\placelistofSORTS`

`\placelistofSYNONYMS`

`\placelocalfootnotes` [OPTIONAL...^{*}.,...]

- * *inherits from* \setupfootnotes

`\placelogos [...,*...]`

OPTIONAL

* IDENTIFIER

`\placeongrid [.1.] {.2.}`

OPTIONAL

1 *inherits from* \moveongrid

2 TEXT

`\placeontopofeachother {.1.} {.2.}`

1 TEXT

2 TEXT

`\placereferencelist [...,*...]`

* IDENTIFIER

`\placeregister [.1.] [...,2,...]`

OPTIONAL

1 IDENTIFIER

2 *inherits from* \setupregister

`\placeREGISTER [...,*,...]`

OPTIONAL

* *inherits from* \setupregister

`\placesidebyside {.1.} {.2.}`

1 TEXT

2 TEXT

`\placesubformula [...,1...] {.2.} $$3.$$`

OPTIONAL

OPTIONAL

1 REFERENCE

2 TEXT

3

`\position (...1,...) {.2.}`

1 POSITION

2 TEXT

`\processblocks [...,1...] [...,2,...]`

OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

`\processpage [...,1...] [...,2,...]`

1 IDENTIFIER

2 yes no

`\program [...]`

* IDENTIFIER

`\publication [...]`

* REFERENCE

`\quotation {...}`

* TEXT

`\quote {...}`

* TEXT

`\ran {...}`

* TEXT

`\ref [..1.] [..2.]`

1 t p r s e
2 REFERENCE

`\reference [..1.] {...2.}`

1 REFERENCE
2 TEXT

`\referral [...,*,...]`

* bet = TEXT
ken = TEXT
dat = TEXT
van = TEXT
aan = TEXT
ref = TEXT

`\referraldate`

`\REGISTER [..1.] {...2.+...}`
OPTIONAL

1 TEXT
2 ENTRY

`\reserveFLOAT [...,.1.,...] [..2.] [...,3,...] {...4.}`
OPTIONAL OPTIONAL OPTIONAL

1 height = DIMENSION
width = DIMENSION
frame = on off
2 TEXT
3 REFERENCE
4 TEXT

`\reset [...;...]`

* IDENTIFIER

`\resetmarking [...]`

* IDENTIFIER

`\resettextrcontent [...1] [...2] [...3]`
OPTIONAL

1 top header text footer bottom

2 text margin edge

3 lefttext middletext righttext

`\rightaligned {...}`

* TEXT

`\Romannumerals {...}`

* TEXT

`\romannumerals {...}`

* TEXT

`\rotate [...,1,...] {...2}`
OPTIONAL

1 inherits from \setuprotate

2 TEXT

`\scale [...,1,...] {...2}`
OPTIONAL

1 sx = NUMBER

sy = NUMBER

2 TEXT

`\screen`

`\section [...;1,...] {...2}`
OPTIONAL

1 REFERENCE

2 TEXT

`\seeREGISTER [...1] {...2} {...3...}`
OPTIONAL

1 TEXT

2 TEXT

3 ENTRY

```
\selectblocks [...,1...] [...,2...] [...,3.]  
                                OPTIONAL  OPTIONAL
```

```
1 IDENTIFIER  
2 IDENTIFIER  
3 criterium = all SECTION
```

```
\selectpaper [...,*,...]
```

```
* family = 1 2
```

```
\selectversion
```

```
\setttextcontent [...1.] [...2.] [...3.] [...4.] [...5.]  
                                OPTIONAL  OPTIONAL  OPTIONAL
```

```
1 top header text footer bottom  
2 text margin edge  
3 TEXT SECTION date MARK pagenumber  
4 TEXT SECTION date MARK pagenumber  
5 TEXT SECTION date MARK pagenumber
```

```
\setupalign [...,*,...]
```

```
* width left right middle inner outer wide broad height bottom line reset hanging nothanging  
hyphenated nothyphenated lesshyphenation morehyphenation new old normal yes no flushleft flushright  
flushouter flushinner center hz nohz spacing nospacing tolerant verytolerant stretch lefttoright  
righttoleft
```

```
\setuparranging [...,*,...]
```

```
* disable 2*16 2*8 2*4 2*2 2**2 2*2*4 2*4*2 2UP 2DOWN 2SIDE 2TOP mirrored rotated doublesided  
negative background 90 180 270
```

```
\setupbackground [...,*,...]
```

```
* leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
before = COMMAND  
after = COMMAND  
state = start stop  
inherits from \setupframed
```

```
\setupbackgrounds [...1.] [...,2...] [...,3...]  
                                OPTIONAL  OPTIONAL
```

```
1 top header TEXT footer bottom page paper leftpage rightpage  
2 leftedge leftmargin TEXT rightmargin rightedge  
3 state = start stop cd:repeat  
inherits from \setupframed
```

```
\setupblackrules [...,*,...]
```

```
* width = DIMENSION max  
height = DIMENSION max  
depth = DIMENSION max  
alternative = a b  
distance = DIMENSION  
n = NUMBER  
color = IDENTIFIER
```

`\setupblank [.*]`

OPTIONAL

* normal default standard line halfline DIMENSION big medium small fixed flexible global unknown

`\setupblock [...1;...] [...2.,...]`

1 IDENTIFIER

2 before = COMMAND

after = COMMAND

inner = COMMAND

style = normal bold slanted boldslanted type cap small... COMMAND

file = FILE

`\setupbodyfont [...*;...]`

* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt
... 12pt

`\setupbodyfontenvironment [1.] [2.] [...3.,...]`

OPTIONAL

OPTIONAL

1 *inherits from* \definebodyfontenvironment

2 *inherits from* \definebodyfontenvironment

3 *inherits from* \definebodyfontenvironment

`\setupbottom [1.] [...2.,...]`

OPTIONAL

1 *inherits from* \setupheader

2 *inherits from* \setupheader

`\setupbottomtexts [1.] [2.] [3.]`

OPTIONAL

1 text margin edge

2 TEXT SECTION date MARK pagenumber

3 TEXT SECTION date MARK pagenumber

`\setupbuffer [1.] [...2.,...]`

OPTIONAL

1 IDENTIFIER

2 paragraph = NUMBER

before = COMMAND

after = COMMAND

`\setupbuttons [...,*;...]`

* state = start stop

inherits from \setupframed

`\setupcapitals [...,*;...]`

* title = yes no

sc = yes no

`\setupcaption [1.] [...2.,...]`

1 IDENTIFIER

2 *inherits from* \setupcaptions

\setupcaptions [.,.*.,..]

* location = top bottom none high low middle left middle right lefthanging righthanging leftmargin
rightmargin innermargin outermargin
width = fit broad max DIMENSION
minwidth = fit DIMENSION
headstyle = normal bold slanted boldslanted type cap small... COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
number = yes no none
inbetween = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
conversion = numbers characters Characters romannumerals Romannumerals
way = bytext bycd:section
separator = TEXT
stopper = TEXT
command = COMMAND
distance = DIMENSION

\setupclipping [.,.*.,..]

* state = start stop
n = NUMBER
nx = NUMBER
ny = NUMBER
x = NUMBER
y = NUMBER
sx = NUMBER
sy = NUMBER
width = DIMENSION
height = DIMENSION
hoffset = DIMENSION
voffset = DIMENSION
offset = DIMENSION
leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
mp = IDENTIFIER

\setupcolor [.*.]

* IDENTIFIER

\setupcolors [.,.*.,..]

* state = start stop global local
conversion = yes no always
reduction = yes no
rgb = yes no
cmyk = yes no
mpcmyk = yes no
mpspot = yes no
factor = yes no
textcolor = IDENTIFIER
split = c m y k p s no IDENTIFIER
criterium = all none

\setupcolumns [.,.*.,..]

OPTIONAL

* n = NUMBER
ntop = NUMBER
rule = on off
height = DIMENSION
tolerance = verystRICT strict tolerant verytolerant stretch
distance = DIMENSION
balance = yes no
align = text inner outer left right flushleft flushright middle center normal no yes
blank = fixed halfline line flexible big medium small
option = background
direction = left right
inherits from \setupframed

`\setupcombinations [..,*.,..]`

* before = COMMAND
inbetween = COMMAND
after = COMMAND
distance = DIMENSION
height = DIMENSION fit
width = DIMENSION fit
location = top middle bottom left right
align = inner outer left right flushleft flushright middle center normal no yes
style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER

`\setupcombinedlist [..1.] [..,2.,..]`

1 IDENTIFIER
2 level = 1 2 3 4 SECTION current
inherits from \setuplist

`\setupcomment [..,*.,..]`

* state = start stop
width = DIMENSION
height = DIMENSION
color = IDENTIFIER
title = TEXT
space = yes no
symbol = normal New Balloon Addition Help Paragraph Key IDENTIFIER
option = max buffer
margin = DIMENSION
distance = DIMENSION

`\setupdescriptions [...1,...] [...,2.,...]`
OPTIONAL

1 IDENTIFIER
2 style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
width = fit broad DIMENSION
distance = DIMENSION
sample = TEXT
text = TEXT
closesymbol = TEXT
closecommand = \...#1
closesymbol = TEXT
titleleft = TEXT
titleright = TEXT
titledistance = DIMENSION
titlestyle = normal bold slanted boldslanted type cap small... COMMAND
titlecolor = IDENTIFIER
align = inner outer left right flushleft flushright middle center normal no yes
margin = standard yes no DIMENSION
location = left right top serried inmargin inleft inright hanging
headstyle = normal bold slanted boldslanted type cap small... COMMAND
headcolor = IDENTIFIER
headcommand = COMMAND
hang = fit broad NUMBER
before = COMMAND
inbetween = COMMAND
after = COMMAND
indentnext = yes no
indenting = never none not no yes always first next small medium big normal odd even
DIMENSION
command = COMMAND

`\setupenumerations [...1,...] [...,2.,...]`
OPTIONAL

1 IDENTIFIER
2 *inherits from \setupdescriptions*

`\setupexternalfigures [.*.]`

```
* scale      = NUMBER
yscale      = NUMBER
yscale      = NUMBER
factor      = max fit broad
wfactor     = NUMBER max broad fit
hfactor     = NUMBER max broad fit
width       = DIMENSION
height      = DIMENSION
frame       = on off
preset      = yes no
display     = FILE
preview     = yes no
repeat      = yes no
object      = yes no
type        = eps mps pdf tif png jpg mov cd:tex
method      = eps mps pdf tif png jpg mov cd:tex
option      = frame empty test
frames      = on off
ymax        = NUMBER
xmax        = NUMBER
directory   = TEXT
location    = local global default none
maxwidth    = DIMENSION
maxheight   = DIMENSION
conversion  = TEXT
prefix      = TEXT
```

`\setupfield [.1.] [.2,...] [.3,.3,...] [.4,.4,...] [.5,.5,...]`

```
1 IDENTIFIER
2 label horizontal vertical frame
3 inherits from \setupfields
4 see 4
5 see 5
```

`\setupfields [.1,...] [.2,.2,...] [.3,.3,...] [.4,.4,...]`

```
1 reset label horizontal vertical frame
2 n          = NUMBER
distance     = DIMENSION
before       = COMMAND
after        = COMMAND
inbetween    = COMMAND
color        = IDENTIFIER
style        = normal bold slanted boldslanted type cap small... COMMAND
align        = inner outer left right flushleft flushright middle center normal no yes
option       = readonly required protected sorted unavailable hidden printable
clickin      = REFERENCE
clickout     = REFERENCE
regionin     = REFERENCE
regionout    = REFERENCE
afterkey     = REFERENCE
format       = REFERENCE
validate     = REFERENCE
calculate    = REFERENCE
fieldoffset  = DIMENSION
fieldframecolor = IDENTIFIER
fieldbackgroundcolor = IDENTIFIER
inherits from \setupframed
3 inherits from \setupfields
4 inherits from \setupfields
```

`\setupfillinlines [.*,.*,...]`

```
* width      = DIMENSION
margin       = DIMENSION
distance     = DIMENSION
before       = COMMAND
after        = COMMAND
```

`\setupfillinrules [..,*.,..]`

* width = fit broad DIMENSION
distance = DIMENSION
before = COMMAND
after = COMMAND
style = normal bold slanted boldslanted type cap small... COMMAND
n = NUMBER
interlinespace = small medium big
separator = TEXT

`\setupfloat [.1.] [..,2.,..]`

1 IDENTIFIER
2 height = DIMENSION
width = DIMENSION
maxheight = DIMENSION
maxwidth = DIMENSION
minwidth = DIMENSION
default = IDENTIFIER
pageboundaries = LIST
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
location = left middle right
inherits from \setupframed

`\setupfloats [..,*.,..]`

* location = left right middle
width = fit DIMENSION
before = COMMAND
after = COMMAND
margin = DIMENSION
spacebefore = small medium big none
spaceafter = small medium big none
sidespacebefore = small medium big none
sidespaceafter = small medium big none
indentnext = yes no
ntop = NUMBER
nbottom = NUMBER
nlines = NUMBER
default = IDENTIFIER
tolerance = 0 1 2
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
sidealign = normal line
numbering = yes nocheck
inherits from \setupframed

`\setupfloatsplitting [..,*.,..]`

* conversion = numbers characters Characters romannumerals Romannumerals
lines = NUMBER

`\setupfonthandling [.1.] [.2.]`

1 IDENTIFIER
2 *inherits from* \definefonthandling

`\setupfontsynonym [.1.] [.2.]`

1 IDENTIFIER
2 *inherits from* \definefontsynonym

`\setupfooter [..1] [..,2,..]`

OPTIONAL

- 1 *inherits from* `\setupheader`
- 2 *inherits from* `\setupheader`

`\setupfootertexts [..1] [..2] [..3]`

OPTIONAL

- 1 text margin edge
- 2 TEXT SECTION date MARK pagenumber
- 3 TEXT SECTION date MARK pagenumber

`\setupfootnotedefinition [..,*,..]`

- * *inherits from* `\setupdescriptions`

`\setupfootnotes [..,*,..]`

- * conversion = numbers characters Characters romannumerals Romannumerals
- way = bytext bycd:section
- location = page TEXT columns firstcolumn lastcolumn high none
- rule = on off
- before = COMMAND
- after = COMMAND
- width = DIMENSION
- height = DIMENSION
- bodyfont = 5pt ... 12pt small big
- style = normal bold slanted boldslanted type cap small... COMMAND
- distance = DIMENSION
- columndistance = DIMENSION
- margindistance = DIMENSION
- n = NUMBER
- numbercommand = `\...#1`
- textcommand = `\...#1`
- split = tolerant strict verystrict NUMBER
- textstyle = normal bold slanted boldslanted type cap small... COMMAND
- textcolor = IDENTIFIER
- interaction = yes no
- factor = NUMBER
- inherits from* `\setupframed`

`\setupforms [..,*,..]`

- * method = HTML FDF

`\setupformulae [..,*,..]`

- * location = left right
- left = TEXT
- right = TEXT
- align = inner outer left right flushleft flushright middle center normal no yes
- option = middle
- strut = yes no
- distance = DIMENSION
- margin = DIMENSION standard yes no
- align = flushleft flushright middle center
- leftmargin = DIMENSION
- rightmargin = DIMENSION
- indentnext = yes no
- alternative = IDENTIFIER
- spacebefore = DIMENSION
- after = DIMENSION
- separator = TEXT
- conversion = numbers characters Characters romannumerals Romannumerals TEXT

`\setupframed` [¹...] [_{OPTIONAL}...,²_,...]

OPTIONAL

1 IDENTIFIER

2 height = fit broad DIMENSION
width = fit broad fixed local DIMENSION
autowidth = yes no force
offset = none overlay default DIMENSION
location = depth hanging high lohi low top middle bottom keep
option = none empty
strut = yes no global local
align = inner outer left right flushleft flushright middle center normal no yes
bottom = COMMAND
top = COMMAND
frame = on off none overlay
topframe = on off
bottomframe = on off
leftframe = on off
rightframe = on off
frameoffset = DIMENSION
framedepth = DIMENSION
framecorner = round rectangular
frameradius = DIMENSION
framecolor = IDENTIFIER
background = screen color none foreground IDENTIFIER
backgroundscreen = NUMBER
backgroundcolor = IDENTIFIER
backgroundoffset = frame DIMENSION
backgrounddepth = DIMENSION
backgroundcorner = round rectangular
backgroundradius = DIMENSION
depth = DIMENSION
corner = round rectangular
radius = DIMENSION
empty = yes no
foregroundcolor = IDENTIFIER
foregroundstyle = normal bold slanted boldslanted type cap small... COMMAND
rulethickness = DIMENSION

`\setupframedtexts` [¹...] [_{OPTIONAL}...,²_,...]

OPTIONAL

1 IDENTIFIER

2 bodyfont = 5pt ... 12pt small big
style = normal bold slanted boldslanted type cap small... COMMAND
left = COMMAND
right = COMMAND
before = COMMAND
after = COMMAND
inner = COMMAND
linecorrection = on off
depthcorrection = on off
margin = standard yes no
location = left right middle none
indenting = never none not no yes always first next small medium big normal odd even
DIMENSION

inherits from \setupframed

`\setuphead [...1,...] [...2,...]`

1 SECTION

2 style = normal bold slanted boldslanted type cap small... COMMAND
textstyle = normal bold slanted boldslanted type cap small... COMMAND
numberstyle = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
textcolor = IDENTIFIER
numbercolor = IDENTIFIER
number = yes no
ownnumber = yes no
page = left right yes
continue = yes no
header = none empty high nomarking
text = none empty high nomarking
footer = none empty high nomarking
before = COMMAND
inbetween = COMMAND
after = COMMAND
alternative = normal inmargin middle TEXT
hang = none broad fit line NUMBER
command = \...#1#2
numbercommand = \...#1
textcommand = \...#1
deepnumbercommand = \...#1
deeptextcommand = \...#1
prefix = + - TEXT
placehead = yes no empty
incrementnumber = yes no LIST FILE
resetnumber = yes no
file = IDENTIFIER
expansion = yes no command
margintext = yes no
inherits from \setupheads

`\setupheader [1.] [...2,...]`

OPTIONAL

1 TEXT margin edge

2 state = normal stop start empty high none nomarking IDENTIFIER
strut = yes no
style = normal bold slanted boldslanted type cap small... COMMAND
leftstyle = normal bold slanted boldslanted type cap small... COMMAND
rightstyle = normal bold slanted boldslanted type cap small... COMMAND
leftwidth = DIMENSION
rightwidth = DIMENSION
before = COMMAND
after = COMMAND

`\setupheadertexts [1.] [2.] [3.]`

OPTIONAL

1 text margin edge

2 TEXT SECTION date MARK pagenumber

3 TEXT SECTION date MARK pagenumber

`\setupheadnumber [1.] [2.]`

1 SECTION

2 NUMBER +cd:number -cd:number

`\setupheads [...,*,...]`

* sectionnumber = yes NUMBER no
alternative = normal margin middle TEXT paragraph
separator = TEXT
stopper = TEXT
align = inner outer left right flushleft flushright middle center normal no yes
alighttitle = yes float no
tolerance = verystRICT strict tolerant verytolerant stretch
indentnext = yes no
command = \...#1#2
margin = DIMENSION

`\setupheadtext [..1.] [..2.]`
OPTIONAL

1 nl fr en uk de es cz ..
2 IDENTIFIER = TEXT

`\setuphyphenmark [.*.]`

* sign = -- --- - ~ () = /

`\setupindentations [...,1...] [...,2...]]`
OPTIONAL

1 IDENTIFIER
2 style = normal bold slanted boldslanted type cap small... COMMAND
headstyle = normal bold slanted boldslanted type cap small... COMMAND
width = fit DIMENSION
text = TEXT
sample = TEXT
before = COMMAND
after = COMMAND
distance = DIMENSION
separator = TEXT

`\setupindenting [...,*...]]`

* never none not no yes always first next small medium big normal odd even DIMENSION

`\setupinmargin [..1.] [...,2...]]`
OPTIONAL

1 left right NUMBER
2 location = left right both
style = normal bold slanted boldslanted type cap small... COMMAND
before = COMMAND
after = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
line = NUMBER
distance = DIMENSION
separator = TEXT
width = DIMENSION
distance = DIMENSION
stack = yes no
inherits from \setupframed

`\setupinteraction [...,*,...]`

```
* state          = start stop
menu            = on off
page           = yes no
click          = yes no
split          = yes no
display        = new
openaction     = REFERENCE
closeaction    = REFERENCE
openpageaction = REFERENCE
closepageaction = REFERENCE
calculate      = IDENTIFIER
strut          = yes no
width          = DIMENSION
height         = DIMENSION
depth         = DIMENSION
style          = normal bold slanted boldslanted type cap small... COMMAND
color          = IDENTIFIER
contrastcolor  = IDENTIFIER
symbolset      = IDENTIFIER
title          = TEXT
subtitle       = TEXT
author         = TEXT
date           = TEXT
keyword        = TEXT
fieldlayer     = auto IDENTIFIER
```

`\setupinteractionbar [...,*,...]`

```
* state          = start stop
alternative     = a b c d e f g
symbol         = yes no
width          = DIMENSION height fit
height         = DIMENSION height fit
depth          = DIMENSION
color          = IDENTIFIER
step           = NUMBER small medium big
inherits from \setupframed
```

`\setupinteractionmenu [...1,...] [...,2,...]`

```
1 IDENTIFIER
2 before        = COMMAND
after          = COMMAND
inbetween      = COMMAND
left           = COMMAND
right          = COMMAND
middle         = COMMAND
state          = start stop none local
style          = normal bold slanted boldslanted type cap small... COMMAND
color          = IDENTIFIER
contrastcolor  = IDENTIFIER
distance       = overlay DIMENSION
samepage       = yes empty no none
unknownreference = yes empty no none
leftoffset     = DIMENSION
rightoffset    = DIMENSION
topoffset      = DIMENSION
bottomoffset   = DIMENSION
position       = yes no
inherits from \setupframed
```

`\setupinteractionscreen [...,*,...]`

```
* width         = DIMENSION fit max
height         = DIMENSION fit max
backspace      = DIMENSION
topspace       = DIMENSION
horoffset      = DIMENSION
veroffset      = DIMENSION
option         = max fit doublesided bookmark
delay          = NUMBER none
```

`\setupinterlinespace [..]`

OPTIONAL

* reset small medium auto big on off

`\setupinterlinespace [..,*.,..]`

* height = NUMBER
depth = NUMBER
line = DIMENSION
top = NUMBER
bottom = NUMBER

`\setupitemgroup [..] [..] [..,3..] [..,4.,..]`

OPTIONAL

OPTIONAL

OPTIONAL

1 IDENTIFIER
2 NUMBER each
3 standard broad serried packed unpacked nowhite before after stopper joinedup atmargin inmargin
autointro loose repeat SECTION paragraph intext random reverse
4 margin = no standard DIMENSION
leftmargin = no standard DIMENSION
rightmargin = no standard DIMENSION
width = DIMENSION
distance = DIMENSION
factor = NUMBER
items = NUMBER
start = NUMBER
before = COMMAND
inbetween = COMMAND
after = COMMAND
left = TEXT
right = TEXT
beforehead = COMMAND
afterhead = COMMAND
headstyle = normal bold slanted boldslanted type cap small... COMMAND
marstyle = normal bold slanted boldslanted type cap small... COMMAND
symstyle = normal bold slanted boldslanted type cap small... COMMAND
stopper = TEXT
n = NUMBER
symbol = NUMBER
align = inner outer left right flushleft flushright middle center normal no yes
symalign = left right flushleft flushright middle center
indentnext = yes no

`\setupitems [..,*.,..]`

* location = left right inmargin top bottom
symbol = 1 2 ... n a ... TEXT none
width = DIMENSION
n = NUMBER unknown
before = COMMAND
inbetween = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
after = COMMAND

`\setuplabeltext [..] [..]`

OPTIONAL

1 nl fr en uk de es cz ..
2 IDENTIFIER = TEXT

`\setuplanguage [..] [..,2.,..]`

1 nl fr en uk de es cz ..
2 inherits from \installlanguage

`\setuplayout [...,*.,...]`

```
* width           = DIMENSION fit middle
height           = DIMENSION fit middle
backspace       = DIMENSION
topspace        = DIMENSION
margin          = DIMENSION
leftmargin      = DIMENSION
rightmargin     = DIMENSION
header          = DIMENSION
footer          = DIMENSION
top             = DIMENSION
bottom         = DIMENSION
leftedge       = DIMENSION
rightedge      = DIMENSION
headerdistance = DIMENSION
footerdistance = DIMENSION
topdistance    = DIMENSION
bottomdistance = DIMENSION
leftmargindistance = DIMENSION
rightmargindistance = DIMENSION
leftedgedistance = DIMENSION
rightedgedistance = DIMENSION
horoffset      = DIMENSION
veroffset      = DIMENSION
style          = normal bold slanted boldslanted type cap small... COMMAND
color          = IDENTIFIER
marking        = on off color screen TEXT page
location       = left middle right bottom top singlesided doublesided
scale          = DIMENSION
nx             = NUMBER
ny             = NUMBER
dx             = DIMENSION
dy             = DIMENSION
lines         = NUMBER
columns       = NUMBER
columndistance = DIMENSION
grid           = yes no
bottomspace    = DIMENSION
cutspace      = DIMENSION
textdistance   = DIMENSION
textwidth     = NUMBER
textmargin    = DIMENSION
clipoffset    = DIMENSION
page          = IDENTIFIER
paper         = IDENTIFIER
```

`\setuplegend [...,*.,...]`

```
* n             = NUMBER
distance       = DIMENSION
inbetween     = COMMAND
width         = DIMENSION
height        = DIMENSION
location      = right bottom
bodyfont      = 5pt ... 12pt small big
```

`\setuplinenumbering [...,*.,...]`

```
* conversion    = numbers characters Characters romannumerals Romannumerals TEXT
start          = NUMBER
step           = NUMBER
width         = DIMENSION
location      = intext inmargin
style         = normal bold slanted boldslanted type cap small... COMMAND
prefix        = TEXT
referencing   = on off
```

`\setuplines [..,*.,..]`

* before = COMMAND
after = COMMAND
inbetween = COMMAND
indenting = never none not no yes always first next small medium big normal odd even DIMENSION
space = yes no

`\setuplinewidth [..*.]`

* DIMENSION

`\setuplist [...,1...] [...,2.,...]`

1 IDENTIFIER
2 state = start stop
alternative = a b c ... none command
coupling = on off
criterium = SECTION local previous current all
pageboundaries = LIST
style = normal bold slanted boldslanted type cap small... COMMAND
numberstyle = normal bold slanted boldslanted type cap small... COMMAND
textstyle = normal bold slanted boldslanted type cap small... COMMAND
pagestyle = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
command = \...#1#2#3
numbercommand = \...#1
textcommand = \...#1
pagecommand = \...#1
interaction = cd:sectionnumber TEXT pagenummer all
before = COMMAND
after = COMMAND
inbetween = COMMAND
left = TEXT
right = TEXT
label = yes no
prefix = yes no none
pagenumber = yes no
headnumber = yes no
cd:sectionnumber = yes no
aligntitle = yes no
margin = DIMENSION
width = DIMENSION fit
height = DIMENSION fit broad
depth = DIMENSION fit broad
distance = DIMENSION
separator = TEXT
stopper = TEXT
symbol = none 1 2 3 ...
expansion = yes no command
maxwidth = DIMENSION
inherits from \setupframed

`\setuplistalternative [.1.] [...,2.,...]`

1 a b c
2 command = COMMAND
width = DIMENSION
stretch = DIMENSION
distance = DIMENSION

`\setupmakeup [1.] [2.,.,.]`

1 IDENTIFIER
2 width = DIMENSION
height = DIMENSION
voffset = DIMENSION
hoffset = DIMENSION
page = left yes right
commands = COMMAND
doublesided = yes no empty
headerstate = normal stop start empty none nomarking
footerstate = normal stop start empty none nomarking
textstate = normal stop start empty none nomarking
topstate = stop start
bottomstate = stop start
pagestate = stop start
color = IDENTIFIER

`\setupmarginblocks [.,.*.,.]`

* location = inmargin left middle right
style = normal bold slanted boldslanted type cap small... COMMAND
width = DIMENSION
align = inner outer left right flushleft flushright middle center normal no yes
top = COMMAND
inbetween = COMMAND
bottom = COMMAND
left = COMMAND
right = COMMAND
before = COMMAND
after = COMMAND

`\setupmarginrules [.*.]`

* level = NUMBER
rulethickness = DIMENSION

`\setupmarking [1.] [2.]`

1 IDENTIFIER
2 state = start stop
separator = COMMAND
expansion = yes no

`\setupnarrower [.,.*.,.]`

* left = DIMENSION
right = DIMENSION
middle = DIMENSION

`\setupnumbering [.,.*.,.]`

* way = bytext bycd:section
state = start stop

`\setupoppositeplacing [.*.]`

* state = start stop
before = COMMAND
inbetween = COMMAND
after = COMMAND

`\setupoutput [...,*,...]`

* IDENTIFIER

`\setuppagenumber [...,*,...]`

* number = NUMBER
state = start stop keep

`\setuppagenumbering [...,*,...]`

* alternative = singlesided doublesided
location = header footer left right middle margin marginedge inleft inright
conversion = numbers characters Characters romannumerals Romannumerals
style = normal bold slanted boldslanted type cap small... COMMAND
left = TEXT
right = TEXT
way = bytext bycd:section
text = TEXT
numberseparator = TEXT
textseparator = TEXT
cd:sectionnumber = yes no
separator = TEXT
strut = yes no
state = start stop
width = DIMENSION
command = \...#1

`\setuppagetransitions [...,*,...]`
OPTIONAL

* reset NUMBER

`\setuppalet [...*...]`

* IDENTIFIER

`\setuppaper [...,*,...]`

* paper = IDENTIFIER
page = IDENTIFIER
nx = NUMBER
ny = NUMBER
width = DIMENSION
height = DIMENSION
topspace = DIMENSION
backspace = DIMENSION
option = max fit
method = normal IDENTIFIER

`\setuppapersize [...1,...] [...2,...]`
OPTIONAL

1 A3 A4 A5 A6 letter ... CD IDENTIFIER landscape mirrored rotated 90 180 270
2 negative *inherits from \setuppapersize*

`\setupparagraphnumbering [...,*,...]`

* state = start stop reset line
style = normal bold slanted boldslanted type cap small... COMMAND
distance = DIMENSION

```
\setupparagraphs [1.] [2.] [3.,.,.]  
                OPTIONAL
```

```
1 IDENTIFIER  
2 NUMBER each  
3 style      = normal bold slanted boldslanted type cap small... COMMAND  
width       = DIMENSION  
height      = DIMENSION  
align       = inner outer left right flushleft flushright middle center normal no yes  
tolerance   = verystRICT strict tolerant verytolerant stretch  
distance    = DIMENSION  
before      = COMMAND  
after       = COMMAND  
inner       = COMMAND  
command     = COMMAND  
rule        = on off
```

```
\setuppositioning [3.,.,.]
```

```
* state = start overlay  
unit    = cm pt em mm ex es in  
factor  = NUMBER  
scale   = NUMBER  
offset  = yes no  
xstep   = absolute relative  
ystep   = absolute relative
```

```
\setupprofiles [3.,.,.]
```

```
* option = test
```

```
\setupprograms [3.,.,.]
```

```
* directory = TEXT
```

```
\setuppuplications [3.,.,.]
```

```
* alternative = apa normal  
inherits from \setupenumerations
```

```
\setupquote [3.,.,.]
```

```
* before = COMMAND  
after    = COMMAND  
style    = normal bold slanted boldslanted type cap small... COMMAND  
color    = IDENTIFIER  
location = TEXT margin
```

```
\setupreferencelist [1.] [2.,.,.]  
                    OPTIONAL
```

```
1 IDENTIFIER  
2 state = start stop  
criterium = SECTION local previous all  
command   = COMMAND  
before    = COMMAND  
after     = COMMAND
```

`\setupreferencing [...,*,...]`

```
* state = start stop
cd:sectionnumber = yes no
prefix = + - TEXT
interaction = label TEXT all symbol
width = DIMENSION
left = COMMAND
right = COMMAND
convertfile = yes no small big
separator = TEXT
autofile = yes no page
global = yes no
```

`\setupregister [.1.] [.2.] [...,3,...]`
OPTIONAL

```
1 SINGULAR NAME
2 IDENTIFIER
3 n = NUMBER
balance = yes no
align = inner outer left right flushleft flushright middle center normal no yes
style = normal bold slanted boldslanted type cap small... COMMAND
pagestyle = normal bold slanted boldslanted type cap small... COMMAND
textstyle = normal bold slanted boldslanted type cap small... COMMAND
indicator = yes no
coupling = yes no
cd:sectionnumber = yes no
criterium = SECTION local all
distance = DIMENSION
symbol = 1 2 ... n a ... none
interaction = page number TEXT
expansion = yes no command
referencing = on off
command = \...#1
location = left middle right
maxwidth = DIMENSION
unknownreference = empty none
alternative = a b A B
prefix = both first none
compress = no yes
deeptextcommand = \...#1
```

`\setuprotate [...,*,...]`

```
* rotation = NUMBER
location = normal high fit broad depth
inherits from \setupframed
```

`\setupscreens [...,*,...]`

```
* method = dot rule external
resolution = NUMBER
factor = NUMBER
screen = NUMBER
```

`\setupsection [.1.] [.2.] [...,3,...]`
OPTIONAL

```
1 IDENTIFIER
2 IDENTIFIER
3 conversion = numbers characters Characters romannumerals Romannumerals
previousnumber = yes no
```

`\setupsectionblock [..1.] [..,2.,..]`

1 IDENTIFIER
2 number = yes no
page = yes right
before = COMMAND
after = COMMAND

`\setupsorting [..1.] [..,2.,..]`

1 IDENTIFIER
2 before = COMMAND
after = COMMAND
command = \...#1
state = start stop
criterium = all used
style = normal bold slanted boldslanted type cap small... COMMAND
expansion = yes no command

`\setupspacing [.*.]`

* broad packed

`\setupstrut [.*.]`

* yes no cap TEXT

`\setupsubpagenumber [..,*.,..]`

* way = bytext bycd:section
state = start stop none

`\setupsymbolset [.*.]`

* IDENTIFIER

`\setupsynchronization [..,*.,..]`

* state = start stop

`\setupsynchronizationbar [..,*.,..]`

* alternative = page local
width = DIMENSION height fit
height = DIMENSION
style = normal bold slanted boldslanted type cap small... COMMAND
color = IDENTIFIER
inherits from \setupframed

`\setupsynonyms [..1.] [..,2.,..]`

1 IDENTIFIER
2 textstyle = normal bold slanted boldslanted type cap small... COMMAND
synonymstyle = normal bold slanted boldslanted type cap small... COMMAND
location = left right top serried inmargin inleft inright
width = DIMENSION
state = start stop
criterium = all used
conversion = yes no
expansion = yes no command
command = \...#1#2#3

`\setupsystem [...,*,...]`

* resolution = NUMBER
file = TEXT
directory = TEXT
random = normal small medium big NUMBER

`\setuptab [...,*,...]`

* sample = TEXT
width = DIMENSION
headstyle = normal bold slanted boldslanted type cap small... COMMAND
location = left right

`\setuptables [...,*,...]`

* distance = small medium big
bodyfont = 5pt ... 12pt small big
HL = NUMBER small medium big none
VL = NUMBER small medium big none
depth = NUMBER strut
height = NUMBER strut
rulethickness = DIMENSION
rulecolor = IDENTIFIER
align = inner outer left right flushleft flushright middle center normal no yes
commands = COMMAND
align = inner outer left right flushleft flushright middle center normal no yes
background = screen color none
backgroundscreen = NUMBER
backgroundcolor = IDENTIFIER
bodyfont = 5pt ... 12pt small big

`\setuptabulate [.1.] [...,2,...]`
OPTIONAL

1 IDENTIFIER
2 unit = DIMENSION
indenting = never none not no yes always first next small medium big normal odd even
DIMENSION
before = COMMAND
after = COMMAND
inner = COMMAND
EQ = TEXT
rulecolor = IDENTIFIER
align = inner outer left right flushleft flushright middle center normal no yes
rulethickness = DIMENSION
distance = blank grid depth DIMENSION small medium big none
bodyfont = 5pt ... 12pt small big
rule = normal line
split = yes no

`\setuptext [.1.] [...,2,...]`
OPTIONAL

1 inherits from \setupheader
2 inherits from \setupheader

`\setuptextrules [...,*,...]`

* location = left inmargin
before = COMMAND
after = COMMAND
inbetween = COMMAND
width = DIMENSION
distance = DIMENSION
bodyfont = 5pt ... 12pt small big
color = IDENTIFIER
style = normal bold slanted boldslanted type cap small... COMMAND
rulecolor = IDENTIFIER

`\setuptexttexts [1.] [2.] [3.]`

OPTIONAL

- 1 `text` margin edge
- 2 TEXT SECTION date MARK pagenumber
- 3 TEXT SECTION date MARK pagenumber

`\setupthinrules [.*.]`

- * interlinespace = small medium big
- n = NUMBER
- before = COMMAND
- inbetween = COMMAND
- after = COMMAND
- color = IDENTIFIER
- backgroundcolor = IDENTIFIER
- height = DIMENSION max
- depth = DIMENSION max
- alternative = a b c d
- rulethickness = DIMENSION
- color = IDENTIFIER
- background = color
- backgroundcolor = IDENTIFIER

`\setuptolerance [...,*...]`

- * horizontal vertical stretch space verystrict strict tolerant verytolerant

`\setuptop [1.] [...,.2.,...]`

OPTIONAL

- 1 *inherits from* `\setupheader`
- 2 *inherits from* `\setupheader`

`\setuptoptexts [1.] [2.] [3.]`

OPTIONAL

- 1 `text` margin edge
- 2 TEXT SECTION date MARK pagenumber
- 3 TEXT SECTION date MARK pagenumber

`\setuptype [...,*...]`

- * space = on off
- option = slanted normal none
- style = normal bold slanted boldslanted type cap small... COMMAND
- color = IDENTIFIER

`\setuptyping` [¹...] [₂...,...]]

OPTIONAL

1 file typing IDENTIFIER

2 space = on off

page = yes no

option = slanted normal commands color none

text = yes no

icommand = COMMAND

vcommand = COMMAND

ccommand = COMMAND

before = COMMAND

after = COMMAND

margin = DIMENSION standard yes no

evenmargin = DIMENSION

oddmargin = DIMENSION

blank = DIMENSION small medium big standard halflines line

escape =

space = on off

tab = NUMBER yes no

page = yes no

indentnext = yes no

style = normal bold slanted boldslanted type cap small... COMMAND

color = IDENTIFIER

palet = IDENTIFIER

lines = yes no hyphenated

empty = yes all no

numbering = line file no

bodyfont = 5pt ... 12pt small big

`\setupunderbar` [...,*...]]

* alternative = a b c

rulethickness = DIMENSION

bottomoffset = DIMENSION

topoffset = DIMENSION

rulecolor = IDENTIFIER

`\setupurl` [...,*...]]

* style = normal bold slanted boldslanted type cap small... COMMAND

urlalternative = none both before after

urlspace = yes no

`\setupversions` [...,*...]]

* number = NUMBER

style = normal bold slanted boldslanted type cap small... COMMAND

`\setupwhitespace` [...*]]

OPTIONAL

* none small medium big line fixed fix DIMENSION

`\showbodyfont` [...*...]]

OPTIONAL

* inherits from `\setupbodyfont`

`\showbodyfontenvironment` [...*...]]

OPTIONAL

* inherits from `\setupbodyfont`

`\showcolor` [...*]]

* IDENTIFIER

`\showcolorgroup [..1.] [...2;...]`

1 IDENTIFIER
2 horizontal vertical name value NUMBER

`\showexternalfigures [..,*,...]`
OPTIONAL

* alternative = a b c

`\showfields [...,*,...]`
OPTIONAL

* IDENTIFIER

`\showframe [..*]`
OPTIONAL

* TEXT margin edge

`\showgrid [...1,...] {...2}`
OPTIONAL

1 reset top bottom none all lines frame nonumber right left
2 TEXT

`\showlayout`

`\showmakeup`

`\showpalet [..1.] [...2;...]`

1 IDENTIFIER
2 horizontal vertical name value

`\showprint [...1,...] [...2;...] [...,3.,...]`

1 *inherits from* \setuppapersize
2 *inherits from* \setuppapersize
3 *inherits from* \setuplayout

`\showsetups`

`\showstruts`

`\showsymbolset [..*]`

* IDENTIFIER

`\somedline [..*]`

* REFERENCE

`\somewhere {1.} {2.} [3.]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\SORT [1.] {2.}`

- 1 TEXT
- 2 TEXT

`\space`

`\splitfloat [...,1.,...] {2.} {3.}`
OPTIONAL

- 1 *inherits from* \setupfloatsplitting
- 2 TEXT
- 3 TEXT

`\startalignment [...,*...] ... \stopalignment`
OPTIONAL

- * *inherits from* \setupalign

`\startbackground {1.} ... \stopbackground`

- * TEXT

`\startBUFFER [...] ... \stopBUFFER`
OPTIONAL

- * IDENTIFIER

`\startbuffer [...] ... \stopbuffer`
OPTIONAL

- * IDENTIFIER

`\startcolor [...] ... \stopcolor`

- * IDENTIFIER

`\startcolumns [...,1.,...] ... \stopcolumns`
OPTIONAL

- * *inherits from* \setupcolumns

`\startcombination [...] ... \stopcombination`

- * N*M

`\startcomment [1.] [...,2.,...] ... \stopcomment`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupcomment

```
\startcomponent ... \stopcomponent
```

*

```
\startDESCRIPTION {...} ... \stopDESCRIPTION
```

* TEXT

```
\startdocument [...] ... \stopdocument
```

* IDENTIFIER

```
\startENUMERATION
```

```
\startenvironment ... \stopenvironment
```

*

```
\startfact .1. .2. .3. ... \stopfact
```

1 EMPTY

2 EMPTY

3 EMPTY

```
\startfigure [.1.] [.2.] [...,.3.,...] ... \stopfigure
```

1 IDENTIFIER

2 FILE

3 factor = NUMBER
frame = on off

```
\startFLOATtext [.1.] [.2.] {.3.} {.4.} ... \stopFLOATtext  
                  OPTIONAL OPTIONAL
```

1 left right high middle low offset tall

2 REFERENCE

3 TEXT

4 TEXT

```
\startFORMULA
```

```
\startFRAMEDTEXT [.1.] [...,.2.,...] ... \stopFRAMEDTEXT  
                  OPTIONAL          OPTIONAL
```

1 left right middle none

2 inherits from \setupframedtexts

```
\starthiding
```

```
\startinteractionmenu [...] ... \stopinteractionmenu
```

* IDENTIFIER

`\startopposite`

`\startoverlay {1.} {2.} ... \stopoverlay`

1 TEXT
2 TEXT

`\startoverview [...*...] ... \stopoverview`

* IDENTIFIER

`\startpacked [...] ... \stoppacked`
OPTIONAL

* blank

`\startPARAGRAPH`

`\startpositioning`

`\startpostponing`

`\startproduct ... \stopproduct`

*

`\startprofile [...*...] ... \stopprofile`

* IDENTIFIER

`\startproject ... \stopproject`

*

`\startquotation [...*...] ... \stopquotation`

* left middle right

`\startREGISTER [1.] {...2.+...}`
OPTIONAL

1 TEXT
2 ENTRY

`\startsymbolset [...] ... \stopsymbolset`

* IDENTIFIER

`\startsynchroization`

`\starttable [...]` ... `\stoptable`

* TEXT IDENTIFIER

`\starttables [...]` ... `\stoptables`

* TEXT IDENTIFIER

`\startTABULATE [...]` ... `\stopTABULATE`
OPTIONAL OPTIONAL

1 TEXT

2 *inherits from \setupexternalfigures*

`\starttextrule [...]` `{...}` ... `\stoptextrule`
OPTIONAL OPTIONAL

1 top bottom

2 TEXT

`\startTYPING`

`\startunpacked`

`\startversion [...,*,...]` ... `\stopversion`

* NUMBER

`\stretched {...}`

* WORD

`\sub [...,*,...]`
OPTIONAL

* REFERENCE

`\subject [...1,...] {...2}`
OPTIONAL

1 REFERENCE

2 TEXT

`\subsection [...1,...] {...2}`
OPTIONAL

1 REFERENCE

2 TEXT

`\subsubject [...1,...] {...2}`
OPTIONAL

1 REFERENCE

2 TEXT


```
\textrule [.1.] {.2.}
           OPTIONAL OPTIONAL
```

- 1 top bottom
- 2 TEXT

```
\thinrule
```

```
\thinrules [.*.]
            OPTIONAL
```

- * inherits from \setupthinrules

```
\title [...;...] {.2.}
          OPTIONAL
```

- 1 REFERENCE
- 2 TEXT

```
\tooltip [.1.] {.2.} {.3.}
          OPTIONAL
```

- 1 left right middle
- 2 TEXT
- 3 TEXT

```
\translate [..,*.,..]
```

- * IDENTIFIER = TEXT

```
\typ {...}
```

- * TEXT

```
\type {...}
```

- * TEXT

```
\typebuffer [.*.]
```

- * IDENTIFIER

```
\typefile [.1.] {.2.}
           OPTIONAL
```

- 1 IDENTIFIER
- 2 TEXT

```
\underbar {...}
```

- * TEXT

```
\underbars {...*...}
```

- * WORD

```
\useblocks [...,1...] [...,2...]
                                OPTIONAL
```

- 1 IDENTIFIER
- 2 IDENTIFIER

```
\usecommands {...}
```

- * TEXT

```
\usedirectory [...,*...]
```

- * IDENTIFIER reset

```
\useencoding [...,*...]
```

- * IDENTIFIER

```
\useexternaldocument [1.] [2.] [3.]
```

- 1 IDENTIFIER
- 2 file
- 3 TEXT

```
\useexternalfigure [1.] [2.] [3.] [...,4.,...]
                   OPTIONAL   OPTIONAL   OPTIONAL
```

- 1 IDENTIFIER
- 2 FILE
- 3 IDENTIFIER
- 4 *inherits from \setupexternalfigures*

```
\useexternalfile [1.] [2.] [3.] [...,4.,...]
```

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 FILE
- 4 bodyfont = 5pt ... 12pt small big

```
\useexternalfiles [1.] [...,2.,...]
```

- 1 IDENTIFIER
- 2 bodyfont = 5pt ... 12pt small big
file = FILE

```
\useexternalsoundtrack [1.] [2.]
```

- 1 IDENTIFIER
- 2 FILE

```
\usemodule [...,*...]
```

- * IDENTIFIER

`\userreferences [...*...]`

* FILE

`\usespecials [...*...]`

* reset IDENTIFIER

`\usesymbols [...*...]`

* IDENTIFIER

`\usetypectscript [...1...] [...2...] [...3...]`

OPTIONAL OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

3 IDENTIFIER

`\usetypectscriptfile [...*...]`

* FILE

`\useURL [.1.] [.2.] [.3.] [.4.]`

1 IDENTIFIER

2 TEXT

3 file

4 TEXT

`\version [...*...]`

* final concept temporary

`\v1 [...*...]`

* NUMBER

`\weekday {...*...}`

* TEXT

`\WEEKDAY {...*...}`

* TEXT

`\whitespace`

`\WORD {...*...}`

* WORD

\Word {...}

* WORD

\wordright {...}

* TEXT

\Words {...*...}

* WORD

\WORDS {...*...}

* WORD

\writebetweenlist [.1.] {.2.}

1 SECTION IDENTIFIER

2 TEXT

\writetolist [.1.] {.2.} {.3.}

1 SECTION IDENTIFIER

2 TEXT

3 TEXT

\writetoreferencelist [.1.] {.2.} {.3.}

1 IDENTIFIER

2 TEXT

3 TEXT

\writetoregister [.1.] [.2.] {...³+...}

OPTIONAL

1 SINGULAR NAME

2 TEXT

3 ENTRY



PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com